

Motion detector

IS 2360 ECO

EAN 4007841006556



Functional description

Stylish infrared ceiling sensor with a noticeably compact look. The surface-mounted motion detector with passive infrared sensor technology is the perfect choice for porches and small rooms. It provides a 360° detection zone that can be matched to any specific situation by means of shrouds. With a reach of Ø 7 m, it reliably detects all movements with absolute precision. The precision IR sensor also impresses with its ease of installation.

Technical specifications

Type	Motion detectors
Dimensions (Ø x H)	115 x 50 mm
Mains power supply	230 V, 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Switching zones	664 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,00 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Reach, tangential	Ø 7 m (38 m ²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 min
Switching output 1, resistive	2000 W
Switching output 1, number of LEDs / fluorescent lamps	6 stk.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years