

Motion detector

IS 3360

EAN 4007841049362



Functional description

Large spaces, multi-storey car parks and production buildings with ceiling heights of up to 4 m rarely provide installation surfaces every metre. These environments call for motion detectors with a long reach. Like the IS 3360. It detects any tangential movement within an all-round distance of 20 metres. Even installed at heights of up to 4 metres. In short: one IS 3360 covers an area of more than 1000 m²! STEINEL Infrared technology that keeps its promises.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	65 x 95 x 95 mm
Mains power supply	230 V, 50 / 60 Hz
Power supply, detail	DALI bus
Number of DALI users	3
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Switching zones	1416 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	Ø 40 m (1257 m ²)
Reach, tangential	Ø 40 m (1257 m ²)
Reach, presence	Ø 3 m (7 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	5 s – 15 min
LiveLink values	Light level, Motion detection, Presence detection
Constant-lighting control	No
Basic light level function	No
Settings via	LiveLink app
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9003

<https://www.steinell-professional.de/>

Motion detector

IS 3360

EAN 4007841049362

Manufacturer's Warranty

5 years

Version

LiveLink - surface-mounted, square

Model

LiveLink

Data sheet



Motion detector

IS 3360

EAN 4007841049362

Sensorenerfassungsbereich 1

Image not found or type unknown

