

Reolink Go PT Plus

2K 5MP 4G Pan-Tilt Camera, Battery or Solar Powered, with Person/Vehicle Detection

- 4G LTE Network
- 2K+ 5MP Super HD
- Person/Vehicle Detection

Specifications

| Video & Audio | |
|-----------------------|---|
| Image Sensor | 1/2.7" CMOS sensor |
| Video Resolution | 2880 x 1660 (5 megapixels) @15fps |
| Lens | f=4mm, F1.6 |
| Video Compression | H.265 |
| Field of View | Horizontal: 90° Vertical: 47° Diagonal: 110° |
| Infrared Night Vision | Up to 10 meters (33ft) ; LED: 2pcs/1.2W/850nm (Auto-switching with IR-cut filter) |
| Color Night Vision | 2pcs/2.4W/6500K |
| Audio | two-way audio |
| Power | |
| Battery | 6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature) |
| Solar | Reolink Solar Panel |
| Interface | |

| | |
|--------------------------|---|
| Power Port | USB Type-C port |
| Reset Button | YES |
| Audio In/Out | Built-in microphone and speaker |
| Storage | |
| microSD Card Slot | Supports Max.128GB microSD card (32GB included) |
| Pan & Tilt | |
| PT Angle(Max.) | Pan: 355°; tilt: 140° |
| Preset Points | Supports 1 guard position & up to 32 preset positions |
| 3G/4G Bandwidth | |
| Frequency Bands | <ul style="list-style-type: none"> • Europe Version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 • U.S. Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 • Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8 |
| Software | |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Protocols & Standards | SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P |
| User Access | Max. 12 simultaneous streams (2 main & 10 sub streams) |
| Other Features | |
| Smart Alarm | PIR detection/person detection/vehicle detection/animal detection |
| PIR Detecting Distance | Adjustable up to 10m (33 ft) |
| PIR Detecting Angle | 120° horizontal |
| Recording Modes | Triggered recording |
| Time Lapse | YES |
| Smart Home Compatibility | Google Assistant, Alexa |
| Cloud Storage | |

| | |
|----------------------------|---|
| | Supports Reolink Cloud (available in selected countries) |
| Working Environment | |
| Operating Temperature | -10 to 55° C (14° to 131° F) |
| Weather Resistance | IP64 |
| Mechanical | |
| Size | Φ98 x 112mm (Φ3.7 x 4.4 in) |
| Weight Battery Included | 485 g (17.1 oz) |
| Warranty | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |

Gallery & Specs



1. Speaker
2. IR LEDs
3. Spotlights
4. Daylight Sensor
5. Lens
6. Status LED
7. PIR Motion Sensor
8. Built-in Microphone



1. Antenna
2. USB Port
3. Power Switch
4. Nano SIM Card Slot
5. microSD Card Slot