

DATASHEET

IP68 Connection module Cat.6A 10Gbit/s for AWG22/1-26/1



General data

IP68 cable connector for outdoor installation and direct burial. Integrated Cat.6A insulation displacement technology to facilitate connection. Designed for transmissions up to 500MHz according to ISO/IEC 11801 ClasseA and Data transmission rate up to 10 Gbit/s.

- Easy installation
- Waterproof cable connector of protection class IP68
- Max. Voltage of 125V and max. current of 1.5A
- Cable gland in PG16
- For cables with a diameter of 4,5 mm- 10 mm
- L x D 121.5mm x 28 mm

Technical properties

Assembly	Cable duct
Category	6A (TIA)
Construction type	straight
Model	LSA/LSA
Temperature Range (Operation)	0 - 70 °C
Type of connector	2x LSA

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



DATASHEET

IP68 Connection module Cat.6A 10Gbit/s for AWG22/1-26/1

Available variants

ArtNr.	Bezeichnung	screened
IP68KV6AWP	IP68 Connection module Cat.6A 10Gbit/s for AWG22/1-26/1	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

