

EAN: 6414150069994

www.oras.com/en/products/oras/product/2715F



Single lever washbasin faucet with an Easy-Grip lever, thermostatic control unit, Smart Bidetta and Smart press pad. The Easy-Grip lever is pleasant to touch and adjusts both the water flow and temperature. Thermostatic control unit maintains the requested water temperature when using the Smart press pad. The faucet is equipped with flexible pipes. The function of remote operated Smart Bidetta hand shower: when lifting the hand shower from the holder water starts to flow from the faucet. When pressing the hand shower trigger the water supply transfers from faucet to hand shower. When placing the Smart Bidetta hand shower back to its holder the faucet closes automatically.

- Bathroom
- Single lever, Battery-operated, Bidetta
- Deck mounted
- Chrome
- Fixed spout
- utility shut-off valve with remote control
- Easy-Grip Lever
- Remote operated Smart Bidetta
- Thermostatic cartridge that reacts quickly and precisely to changes in water temperature
- surfaces in contact with drinking water contain less than 0.3% lead

Technical data

Flow properties

Flow-rate at 300 kPa	0.12 l/s
Pressure loss with flow (0.1 l/s)	200 kPa

Technical properties

Hot water supply	max. +70°C
Working pressure	100 - 1000 kPa
Connection size	G1/2 / G3/8
Projection	98 mm
Material	brass

Software settings

Max. flow period	2 min Bidetta, 6 s (4-15 s) press pad
------------------	--

Electronic properties

Battery	AA 1.5 V Lithium x 2, CR 2450 3 V x 2
Number of devices connected	max. 8

Regulations

EMC Directive	CE 2004/108/EY
EN standard	EN 15091 , EN 817
Noise class	I (ISO 3822)
Protection class	IP 55

Type approvals

STF certificate	VTT-RTH-00063-14
ETA-Danmark	VA 1.42/20420
KIWA SE	1462



