

EAN: 6414150082436

www.oras.com/en/products/oras/product/3009F



Single lever washbasin faucet with Bidetta hand shower and Smart press pad. Spout's swing angle is factory preset at 120° (can be limited to 60°-0°). The function of Smart press pad: The washing machine valve is opened by pressing the Smart press pad and the valve closes automatically after preset period. Washing machine valve closes automatically after 4 or 12 hours (one push opens the valve for 4 hours, pushing for 5 seconds opens the valve for 12 hours).

F = with flexible pipes

- Bathroom
- Single lever, Side operated, Battery-operated, Bidetta
- Deck mounted
- Chrome
- PCA® for a constant flow rate regardless of pressure fluctuations, HONEYCOMB® with improved lime protection, CACHE®, without housing directly screwed into the faucet spout
- utility shut-off valve with remote control
- 3S-installation system for safe and simple mounting

Technical data

Flow properties

Flow-rate at 300 kPa (with flow controller)	0.1 l/s
Pressure loss with flow (0.1 l/s)	100 kPa

Technical properties

Hot water supply	max. +70°C
Working pressure	100 - 1000 kPa
Connection size	G3/8
Projection	151 mm
Material	brass

Software settings

Dishwasher valve open period	4h / 12 h
------------------------------	------------------

Electronic properties

Battery	AA 1.5 V Lithium x 2, CR 2450 3 V
---------	--

Regulations

EMC Directive	CE 2014/30/EU
EN standard	EN 817, EN 15091
Noise class	I (ISO 3822)
Protection class	IP 54



