


Floodlight

XLED home 2 SL

EAN 4007841033125



Functional description

The moveable sensor-switched outdoor floodlight with fully swivelling LED panel in a classy opal look. The XLED home 2 sensor-switched floodlight comes in a sophisticated design. It is not just an eye-catcher, but also a truly talented mover. Thanks to the fully swivelling LED panel, every corner of the entrance area can be illuminated flexibly and as required. The highly efficient LED technology coupled with the opal cover provides maximum lighting comfort. As an individual floodlight or interconnected with the slave version, the innovative new generation of the XLED home success series is available in white, black, graphite and silver.

Technical specifications

Dimensions (L x W x H)	181 x 180 x 161 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
Output	14,8 W
Luminous flux	1184 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	HCMC (High Conductive Magnesium Composite)
With motion detector	No
Photo-cell controller	No
Impact resistance	IK00
IP rating	IP44
Protection class	II
Housing material	HCMC
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
PU1, net weight	0,483 kg
Version	white