


Floodlight

XLED home 2 SL

EAN 4007841033101



Functional description

The moveable sensor-switched outdoor floodlight with fully swivelling LED panel in a classy opal look. The XLED home 2 sensor-switched floodlight comes in a sophisticated design. It is not just an eye-catcher, but also a truly talented mover. Thanks to the fully swivelling LED panel, every corner of the entrance area can be illuminated flexibly and as required. The highly efficient LED technology coupled with the opal cover provides maximum lighting comfort. As an individual floodlight or interconnected with the slave version, the innovative new generation of the XLED home success series is available in white, black, graphite and silver.

Technical specifications

| | |
|--|--|
| Dimensions (L x W x H) | 181 x 180 x 161 mm |
| Mains power supply | 230 – 240 V , 50 / 60 Hz |
| Output | 14,8 W |
| Luminous flux | 1184 lm |
| Colour temperature | 4000 K |
| Colour variation LED | SDCM3 |
| Colour Rendering Index CRI | 80-89 |
| With lamp | Yes, STEINEL LED system |
| Lamp | LED cannot be replaced |
| LED life expectancy (max. °C) | 50000 h |
| Drop in luminous flux in accordance with LM80 | L70B10 |
| LED cooling system | HCMC (High Conductive Magnesium Composite) |
| With motion detector | No |
| Photo-cell controller | No |
| Impact resistance | IK00 |
| IP rating | IP44 |
| Protection class | II |
| Housing material | HCMC |
| Cover material | Plastic, opal |
| Manufacturer's Warranty | 5 years |
| PU1, net weight | 0,483 kg |
| Version | Silver |