


Indoor light

RS PRO 5850 LED

EAN 4007841007676



Functional description

Same perfection. Even more luminous power. In the 45W version too, this linear luminaire from the RS PRO range offers advanced technologies and Germany's best development expertise by the metre.

Technical specifications

Dimensions (L x W x H)	1,583 x 105 x 105 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Output	45 W
Luminous flux	5570 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Photo-cell controller	Yes
Functions	Group parameterisation, Neighbouring-light function, Presence function
Soft light start	Yes
Impact resistance	IK07
IP rating	IP66
Protection class	I
Ambient temperature	-20 – 30 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	Sensor

Indoor light

RS PRO 5850 LED

EAN 4007841007676

Light distribution curve 1

Sensorenerfassungsbereich 1

