

## Indoor light

# RS PRO 5500 Slave

EAN 4007841749910



## Functional description

In broad, long corridors light is not just a matter of function but also of good design. The RS PRO 5500 pleases the discerning eye with its slender design. As does a glance at the electricity bill. Fitted with 2 x 28 W T5 tubes, twin electronic ballast and high-frequency sensor system, it makes for energy efficiency. Because it only switches light ON Light only when it's actually needed. Instantly and without flickering. For complex lighting tasks, several RS PRO 5500 luminaires can be interconnected by cable. Also available as a slave version.

## Technical specifications

<b>Dimensions (L x W x H)</b>	1,295 x 163 x 64 mm
<b>Mains power supply</b>	230 – 240 V , 50 / 50 Hz
<b>Output</b>	57 W
<b>With lamp</b>	No
<b>Lamp</b>	Fluorescent lamp D=16 mm
<b>Base</b>	T5
<b>With motion detector</b>	No
<b>Photo-cell controller</b>	No
<b>Impact resistance</b>	IK07
<b>IP rating</b>	IP44
<b>Protection class</b>	I
<b>Ambient temperature</b>	-10 – 50 °C
<b>Housing material</b>	Plastic
<b>Cover material</b>	Plastic, transparent
<b>Manufacturer's Warranty</b>	5 years

Indoor light

# RS PRO 5500 Slave

EAN 4007841749910

## Light distribution curve 1

