


Indoor light

RS PRO LED S2

EAN 4007841035846



Functional description

Same design as RS PRO LED S1, just larger in diameter. And with an even more powerful 26 W STEINEL LED lighting system. Apart from that, the RS PRO LED S2 comes with exactly the same impressive line-up as its little sister. Put simply: convenient adjustment by Smart Remote, no unintentional deactivation thanks to presence mode and neighbouring-light function that moves along with the person walking past to illuminate the way ahead.

Technical specifications

Dimensions (Ø x H)	350 x 83 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	26 W
Interconnection	Yes
Luminous flux	2496 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Base	without
LED cooling system	Active Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Basic light level function	Yes
Basic light level function time	all night, 10/30 min
Functions	Neighbouring-light function, Presence function
Impact resistance	IK03
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	5 years

Data sheet



Indoor light

RS PRO LED S2

EAN 4007841035846

Version

PMMA warm white

Indoor light

RS PRO LED S2

EAN 4007841035846

Light distribution curve 1

Sensorenerfassungsbereich 1

