


Indoor light

RS LED M2

EAN 4007841052508



Functional description

Even more design options for sophisticated residential environments. LED indoor lights with integrated high-frequency sensor in a material translucent throughout impress with a light output of 873 lm for optimum illumination and classy ambient light. And the consumption of just 9,5 W is also impressive. With convenient night light function (10 %) and 4-hour manual override. The RS LED M2 comes in two attractive design versions.

Technical specifications

Dimensions (L x W x H)	220 x 220 x 67 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Output	9,5 W
Interconnection	Yes
Luminous flux	873 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	65000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 30 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	3 years

<https://www.steinell.de/>

Data sheet



Indoor light

RS LED M2

EAN 4007841052508

Version

Chrome
