


Indoor light

RS LED M2

EAN 4007841052515



Functional description

Even more design options for sophisticated residential environments. LED indoor lights with integrated high-frequency sensor in a material translucent throughout impress with a light output of 873 lm for optimum illumination and classy ambient light. And the consumption of just 9,5 W is also impressive. With convenient night light function (10 %) and 4-hour manual override. The RS LED M2 comes in two attractive design versions.

Technical specifications

Dimensions (L x W x H)	220 x 220 x 67 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	9,5 W
Interconnection	Yes
Luminous flux	873 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	65000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 30 °C
Housing material	Plastic

<https://www.steinell.de/>

Indoor light

RS LED M2

EAN 4007841052515

Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Version	Silver