


## Outdoor light

# DL Vario Quattro PRO LED

EAN 4007841057589



## Functional description

The LED ceiling light with precise detection. The four infrared sensors can be mechanically adjusted to cover any distance from 2 to 8 m. 360° all-round detection is ideally suited for optimum adjustment to the local situation, e.g. carports and porches. The light diffuser also acts as the sensor lens - a patented world first. The ceiling light provides 1430 lm of illumination at an output of 14 W and can be mounted at heights of up to 6 m, including a convenient basic light level function (10%) at twilight. The DL Vario Quattro PRO LED can easily be connected to the network via cable (up to 10 lights). Available in neutral white (4000K) and warm white (3000K) colour temperature.

## Technical specifications

<b>Dimensions (Ø x H)</b>	310 x 69 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>max</b>	6,00 m
<b>Sensor Technology</b>	passive infrared
<b>Output</b>	14 W
<b>Interconnection</b>	Yes
<b>Luminous flux</b>	1430 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Base</b>	without
<b>LED cooling system</b>	Passive Thermo Control
<b>With motion detector</b>	Yes
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	180 °
<b>Sneak-by guard</b>	Yes
<b>Capability of masking out individual segments</b>	No
<b>Electronic scalability</b>	No
<b>Mechanical scalability</b>	Yes
<b>Reach, detail</b>	Reichweite von 2 - 8 m in 4 Richtungen (je 90 °) einstellbar
<b>Reach, radial</b>	4 x 4 m (16 m²)
<b>Reach, tangential</b>	16 x 16 m (256 m²)
<b>Photo-cell controller</b>	Yes
<b>Twilight setting</b>	2 – 1000 lx
<b>Time setting</b>	5 s – 30 min
<b>Basic light level function</b>	Yes
<b>Basic light level function time</b>	10/30 min, all night
<b>Soft light start</b>	Yes
<b>Continuous light</b>	selectable, 4h
<b>Impact resistance</b>	IK07

<https://www.steinell-professional.de/>

Outdoor light

# DL Vario Quattro PRO LED

EAN 4007841057589

<b>IP rating</b>	IP54
<b>Protection class</b>	II
<b>Ambient temperature</b>	-20 – 35 °C
<b>Housing material</b>	Plastic
<b>Cover material</b>	Plastic, structured
<b>Manufacturer's Warranty</b>	5 years
<b>With remote control</b>	No
<b>Version</b>	Neutral white anthracite