


Indoor light

RS PRO Connect 5100 LED

EAN 4007841052904



Functional description

Our engineers were sure about this: the new diffuser luminaire was supposed to be simple and good. Easy to install, easy to maintain, and top notch in terms of efficiency, function and quality. The result: RS PRO Connect 5100 LED. The diffuser luminaire the world has been waiting for. Sturdy, highly practical, extremely easy to install, wirelessly interconnectable and, ultimately, conveniently configured via the smartphone.

Technical specifications

Dimensions (L x W x H)	1,370 x 87 x 58 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Output	30 W
Interconnection	Yes
Luminous flux	4310 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	60000 h
LED cooling system	Passive Thermo Control
With motion detector	No
Electronic scalability	Yes
Photo-cell controller	No
Basic light level function	Yes
Basic light level function time	10-30 min, all night
Impact resistance	IK07
IP rating	IP66
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, structured
Manufacturer's Warranty	5 years
Version	Slave