


Indoor light

# RS PRO Connect 5100 LED

EAN 4007841052911



## Functional description

Our engineers were sure about this: the new diffuser luminaire was supposed to be simple and good. Easy to install, easy to maintain, and top notch in terms of efficiency, function and quality. The result: RS PRO Connect 5100 LED. The diffuser luminaire the world has been waiting for. Sturdy, highly practical, extremely easy to install, wirelessly interconnectable and, ultimately, conveniently configured via the smartphone.

## Technical specifications

<b>Dimensions (L x W x H)</b>	1,370 x 87 x 58 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>Sensor Technology</b>	High frequency
<b>Output</b>	30 W
<b>Interconnection</b>	Yes
<b>Luminous flux</b>	4206 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	60000 h
<b>LED cooling system</b>	Passive Thermo Control
<b>With motion detector</b>	Yes
<b>Detection</b>	also through glass, wood and stud walls
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	160 °
<b>Electronic scalability</b>	Yes
<b>Mechanical scalability</b>	No
<b>Photo-cell controller</b>	Yes
<b>Twilight setting</b>	2 – 2000 lx
<b>Time setting</b>	5 s – 60 min
<b>Basic light level function</b>	Yes
<b>Basic light level function time</b>	10-30 min, all night
<b>Functions</b>	Neighbouring-light function, Presence function, Group parameterisation
<b>Impact resistance</b>	IK07
<b>IP rating</b>	IP66
<b>Protection class</b>	II
<b>Ambient temperature</b>	-20 – 40 °C
<b>Housing material</b>	Plastic
<b>Cover material</b>	Plastic, structured
<b>Manufacturer's Warranty</b>	5 years
<b>Settings via</b>	Bluetooth
<b>With remote control</b>	Yes

<https://www.steinell-professional.de/>

Data sheet



Indoor light

# RS PRO Connect 5100 LED

EAN 4007841052911

Version

Sensor

---