


Outdoor Lights

L 710 LED

EAN 4007841053185



Functional description

The L 710 LED outdoor light scores with a trailblazing design. In connection with the elegant light gradient, the futuristic shape of the light creates a unique light pattern. The warm-white light (3000 K) adds a harmonious air to the overall sculptured effect. The L 710 LED outdoor light is fitted with an intelligent 360° infrared sensor and has four sensor programs, including night-light functions and soft light start. In the manual override mode, the L 710 LED stays ON for four hours. A second version is also available without motion detector - the LN 710 LED. This version is fitted with a photo-cell controller and provides automatic illumination at night, as well as an optional night economy mode.

Technical specifications

Dimensions (L x W x H)	260 x 140 x 77 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Mounting height max.	2,50 m
Sensor Technology	passive infrared
Output	8,6 W
Interconnection	No
Luminous flux	670 lm
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	360 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, tangential	r = 8 m (201 m²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min
Basic light level function	Yes
Soft light start	Yes
Continuous light	selectable, 4h
Impact resistance	IK03
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal

<https://www.steinell.de/>

Outdoor Lights

L 710 LED

EAN 4007841053185

Manufacturer's Warranty	3 years
With remote control	No
Cover material	sticker
Version	Anthracite