


## Outdoor light

# L 920 LED

EAN 4007841056490



### Functional description

The ideal accent lighting. Designed as a classic uplight/downlight, the L 920 LED sensor-switched outdoor light immerses house walls in a comfortable 3000 K warm-white light, and with 516 lm at just 10 W creates a friendly and inviting lighting mood. The 140° infrared sensor provides a reach of 12 m. If interconnected with several lights, the lights are switched simultaneously. The L 920 LED features various night light functions as well as an optional 4-hour manual override.

### Technical specifications

<b>Dimensions (L x W x H)</b>	225 x 95 x 94 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>max</b>	2,50 m
<b>Sensor Technology</b>	passive infrared
<b>Output</b>	10 W
<b>Interconnection</b>	Yes
<b>Luminous flux</b>	571 lm
<b>Colour temperature</b>	3000 K
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Base</b>	without
<b>LED cooling system</b>	Passive Thermo Control
<b>With motion detector</b>	Yes
<b>Detection angle</b>	140 °
<b>Sneak-by guard</b>	No
<b>Capability of masking out individual segments</b>	No
<b>Electronic scalability</b>	Yes
<b>Mechanical scalability</b>	No
<b>Reach, radial</b>	r = 2 m (5 m <sup>2</sup> ) / r = 4 m (20 m <sup>2</sup> )
<b>Reach, tangential</b>	r = 5 m (31 m <sup>2</sup> ) / r = 12 m (176 m <sup>2</sup> )
<b>Photo-cell controller</b>	Yes
<b>Twilight setting</b>	2 – 20 lx
<b>Time setting</b>	120 s – 15 min
<b>Basic light level function</b>	Yes
<b>Basic light level function time</b>	10-30 min, all night
<b>Soft light start</b>	Yes
<b>Continuous light</b>	selectable, 4h
<b>Impact resistance</b>	IK00
<b>IP rating</b>	IP44
<b>Protection class</b>	II
<b>Ambient temperature</b>	-20 – 50 °C
<b>Housing material</b>	Aluminium

<https://www.steinell.de/>

Outdoor light

# L 920 LED

EAN 4007841056490

<b>Cover material</b>	Plastic, opal
<b>Manufacturer's Warranty</b>	3 years
<b>With remote control</b>	No
<b>Version</b>	Silver