


## Indoor light

# RS PRO LED S2 IP65

EAN 4007841057688



## Functional description

Same design as the RS PRO LED S1 IP65, just larger in diameter. Besides this, "big brother" is equally as impressive as little sister: IP65 rating, class II protection, impact-resistant to IK10, STEINEL LED lighting system, high-frequency sensor technology, wireless connection, basic light-level function, presence mode and neighbouring light function.

## Technical specifications

<b>Dimensions (Ø x H)</b>	362 x 82 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>Sensor Technology</b>	High frequency
<b>Transmitter power</b>	< 1 mW
<b>Output</b>	26 W
<b>Interconnection</b>	Yes
<b>Luminous flux</b>	1903 lm
<b>Colour temperature</b>	3000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	70000 h
<b>Drop in luminous flux in accordance with LM80</b>	L80B10
<b>Base</b>	without
<b>LED cooling system</b>	Active and Passive Thermo Control
<b>With motion detector</b>	Yes
<b>Detection</b>	also through glass, wood and stud walls
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	160 °
<b>Electronic scalability</b>	Yes
<b>Mechanical scalability</b>	No
<b>Photo-cell controller</b>	Yes
<b>Twilight setting</b>	2 – 2000 lx
<b>Time setting</b>	5 sec – 15 min
<b>Basic light level function</b>	Yes
<b>Basic light level function time</b>	10/30 min, all night
<b>Functions</b>	Neighbouring-light function, Presence function
<b>Impact resistance</b>	IK10
<b>IP rating</b>	IP65
<b>Protection class</b>	II
<b>Ambient temperature</b>	-10 – 50 °C
<b>Housing material</b>	Aluminium
<b>Cover material</b>	Plastic, opal
<b>Manufacturer's Warranty</b>	5 years

<https://www.steinell-professional.de/>

Data sheet



Indoor light

# RS PRO LED S2 IP65

EAN 4007841057688

**Version**

warm white

---

Indoor light

# RS PRO LED S2 IP65

EAN 4007841057688

Light distribution curve 1

Sensorenerfassungsbereich 1

