

# SLC LED STRIP MONO CC 126 5M

## 10MM 15W 1560LM 840 IP54



Professional LED-strip with high efficiency high lumen output. Constant Current technology protects each LED diode against voltage drop and gives more uniform light on long distances

Light technic	
Product ID	S13049
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	15 W/m
Number of nodes per meter	126 LED's
Colour temperature	4000 - 4000 K
Colour of light	White
Luminous flux per meter	1560 lm/m
Rated life time L70/B10 at 25 °C	90000 Hours
Rated life time L70/B50 at 25 °C	110000 Hours
Rated life time L80/B10 at 25 °C	60000 Hours
Rated life time L80/B50 at 25 °C	70000 Hours
Rated life time L90/B10 at 25 °C	29000 Hours
Rated life time L90/B50 at 25 °C	35000 Hours
Lamp power per foot	4.5 W
Number of nodes per foot	37.8
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Cutting point, every	56 mm
IP class	IP54
LED-Strip length	5 m
Max length per connection:	10 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP54
Lamp voltage	24 - 24 V
Max. system power	75 W
Input	
Voltage type	DC
Installation	



28.04.2020

Subject to changes and printing errors

<b>Length of particular segments</b>	56 mm
<b>Height/depth</b>	2.5 mm
<b>Length</b>	5000 mm
<b>Width</b>	10 mm
<b>Mounting method</b>	Surface mounting/recessed mounting
<b>Model</b>	Strip
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Connection type</b>	Solder
<b>Self-adhesive</b>	Yes
<b>Number of poles</b>	2
<b>With protective cover</b>	Yes
<b>With connection set</b>	No
<b>With end piece</b>	No
<b>Type of wiring</b>	Ending
<b>logistics data</b>	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group
<b>General data</b>	
<b>GTIN</b>	7070938056434