

SLC LED STRIP MONO CC 126 10M

10MM 15W 1600LM 840 IP20



Professional LED-strip with high efficiency high lumen output. Constant Current technology protects each LED diode against voltage drop and gives more uniform light on long distances

Light technic	
Product ID	S103146
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	15 W/m
Number of nodes per meter	126 LED's
Colour temperature	4000 - 4000 K
Colour of light	White
Luminous flux per meter	1600 lm/m
Rated life time L70/B10 at 25 °C	90000 Hours
Rated life time L70/B50 at 25 °C	110000 Hours
Rated life time L80/B10 at 25 °C	60000 Hours
Rated life time L80/B50 at 25 °C	70000 Hours
Rated life time L90/B10 at 25 °C	29000 Hours
Rated life time L90/B50 at 25 °C	35000 Hours
Lamp power per foot	4.5 W
Number of nodes per foot	37.8
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Cutting point, every	56 mm
IP class	IP20
LED-Strip length	10 m
Max length per connection:	10 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24 - 24 V
Max. system power	150 W
Input	
Voltage type	DC
Installation	



28.04.2020

Subject to changes and printing errors

Length of particular segments	56 mm
Height/depth	2 mm
Length	10000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	No
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938060745