CE

## SLC LED STRIP RGB CV 60 5M 10MM 14,4W 205LM IP54

RGB is a multicolour LED-strip, which is suitable for colourful, creative installations. Set colour on a special design, give a room a new atmosphere, illuminate a garden, spa, restaurant etc. Available in 3 IP-rating Options.

| Light technic                                    |   |
|--|---|
| Product ID                                       | S14002                                      |
| Beam angle                                       | 120   |
| Lamp type  | LED not exchangeable                        |
| Lamp power per meter                             | 14.4 W/m                                    |
| Number of nodes per meter                        | 60 LED`s                                    |
| Colour of light                                  | RGB   |
| Luminous flux per meter                          | 205 lm/m                                    |
| Rated life time L70/B50 at 25 °C                 | 50000 Hours                                 |
| Lamp power per foot                              | 4.32 W                                      |
| Number of nodes per foot                         | 18  |
| Energy efficiency class of the built-<br>in lamp | A++, A+, A (LED)                            |
| Technical data                                   |   |
| Cutting point, every                             | 100 mm                                      |
| IP class   | IP54  |
| LED-Strip length                                 | 5 m   |
| Max length per connection:                       | 5 meter m                                   |
| Protection class                                 | II  |
| Type of control gear                             | LED operating device voltage-<br>controlled |
| Degree of protection (IP)                        | IP54  |
| Lamp voltage                                     | 24 - 24 V                                   |
| Max. system power                                | 72 W  |
| Power factor                                     | 0.95  |
| Input  |   |
| Voltage type                                     | DC  |
| Installation                                     |   |
| Length of particular segments                    | 100 mm                                      |
| Height/depth                                     | 2.5 mm                                      |
| Length   | 5000 mm                                     |
| Width  | 10 mm                                       |
| Mounting method                                  | Surface mounting/recessed                   |



SLC -

-

H

28.04.2020 Subject to changes and printing errors

|                         | mounting        |
|-------------------------|-----------------|
| Model                   | Strip           |
| Conductor cross section | 0.35 mm2        |
| Connection type         | Solder          |
| Self-adhesive           | Yes             |
| Number of poles         | 4               |
| With protective cover   | No              |
| Lowest bending radius   | 20 mm           |
| With connection set     | No              |
| With end piece          | No              |
| Type of wiring          | Ending          |
| logistics data          |                 |
| Imported by             | The Light Group |
| Brand                   | SLC             |
| General data            |                 |
| D-pack length           | 550 mm          |
| GTIN                    | 7070938056601   |
| Pallet length           | 1200 mm         |
| M-pack length           | 383 mm          |
| F-pack length           | 383 mm          |

28.04.2020 Subject to changes and printing errors