


Indoor light

RS PRO LED S1 IP65

EAN 4007841057794



Functional description

Public buildings, swimming pools, passages, subways and the like are tough environments when it comes to lighting. Because it's here that wet environments, unintentional knocks and vandalism are the order of the day. All this leaves the RS PRO LED S1 IP65 completely indifferent. Its screw-mounted surround is impervious to dust and jets of water. With a shatter-proof interior, shade and enclosure are impact-resistant to IK10 as well. Several LED lights can be wirelessly interconnected – in series, round corners or through floors.

Technical specifications

Dimensions (Ø x H)	300 x 71 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Output	15 W
Luminous flux	1213 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	70000 h
Drop in luminous flux in accordance with LM80	L80B10
Base	without
LED cooling system	Active and Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Continuous light	selectable
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Functions	Manual ON / ON-OFF, Group parameterisation, Neighbouring-light function, Presence function
Impact resistance	IK10
IP rating	IP65
Protection class	II
Ambient temperature	-10 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal

<https://www.steinel-professional.de/>

Indoor light

RS PRO LED S1 IP65

EAN 4007841057794

Manufacturer's Warranty 5 years

With remote control No

Version Neutral white

Indoor light

RS PRO LED S1 IP65

EAN 4007841057794

Light distribution curve 1

Sensorenerfassungsbereich 1

