


Indoor light

RS PRO DL LED 15 W

EAN 4007841007744



Functional description

Only available from STEINEL. The RS PRO LED DL 15 W LED is the first HF-sensor controlled LED downlighter that can be integrated in the ceiling. But there's not a lot of it you can see. Because once in place, the entire system fits flush with the suspended ceiling. In no time at all, thanks to easy-fit clamp-type retainer. Using interconnected slave versions, RS PRO DL 15 W LED provides even greater energy efficiency.

Technical specifications

Dimensions (Ø x H)	142.5 x 88 mm
Mains power supply	100 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	15 W
Output, detail	Only via Eltako ER12DX-UC with basic light function deactivated
Luminous flux	707,4 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Photo-cell controller	Yes
Time setting	60 s – 60 min
Basic light level function time	10 min, 30 min, all night
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	warm white

Indoor light

RS PRO DL LED 15 W

EAN 4007841007744

Light distribution curve 1

Sensorenerfassungsbereich 1

