


Indoor light

RS PRO DL LED 20 W

EAN 4007841007782



Functional description

The RS PRO LED DL 20 W is the more powerful version of the LED downlighter. And there's not much left to see from this indoor ceiling light with high-frequency sensor either. Once in place, the entire system fits flush with the suspended ceiling, with the easy-fit clamp-type retainer making installation a breeze. Incidentally, the energy efficiency of the RS PRO DL LED 20W can be increased even further by using interconnectable slave versions.

Technical specifications

Dimensions (Ø x H)	168 x 88 mm
Mains power supply	100 – 240 V , 50 / 60 Hz
Sensor Technology	High frequency
Transmitter power	< 1 mW
Output	20 W
Output, detail	Only via Eltako ER12DX-UC
Luminous flux	1077 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Electronic scalability	Yes
Mechanical scalability	No
Photo-cell controller	Yes
Time setting	60 s – 60 min
Basic light level function time	10 min, 30 min, all night
Impact resistance	IK00
IP rating	IP20
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	5 years

Data sheet



Indoor light

RS PRO DL LED 20 W

EAN 4007841007782

Version

warm white

Indoor light

RS PRO DL LED 20 W

EAN 4007841007782

Light distribution curve 1

Sensorenerfassungsbereich 1

