


## Indoor light

# RS PRO DL LED 20 W

EAN 4007841007751



## Functional description

The RS PRO LED DL 20 W is the more powerful version of the LED downlighter. And there's not much left to see from this indoor ceiling light with high-frequency sensor either. Once in place, the entire system fits flush with the suspended ceiling, with the easy-fit clamp-type retainer making installation a breeze. Incidentally, the energy efficiency of the RS PRO DL LED 20W can be increased even further by using interconnectable slave versions.

## Technical specifications

<b>Dimensions (Ø x H)</b>	168 x 88 mm
<b>Mains power supply</b>	100 – 240 V , 50 / 60 Hz
<b>Sensor Technology</b>	High frequency
<b>Transmitter power</b>	< 1 mW
<b>Output</b>	20 W
<b>Output, detail</b>	Only via Eltako ER12DX-UC
<b>Luminous flux</b>	1230 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	70-79
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Drop in luminous flux in accordance with LM80</b>	L70B10
<b>Base</b>	without
<b>LED cooling system</b>	Passive Thermo Control
<b>With motion detector</b>	Yes
<b>Detection</b>	also through glass, wood and stud walls
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	160 °
<b>Electronic scalability</b>	Yes
<b>Mechanical scalability</b>	No
<b>Photo-cell controller</b>	Yes
<b>Time setting</b>	60 s – 60 min
<b>Basic light level function time</b>	10 min, 30 min, all night
<b>Impact resistance</b>	IK00
<b>IP rating</b>	IP20
<b>Protection class</b>	II
<b>Ambient temperature</b>	-10 – 40 °C
<b>Housing material</b>	Aluminium
<b>Cover material</b>	Plastic, opal
<b>Manufacturer's Warranty</b>	5 years

Data sheet



Indoor light

# RS PRO DL LED 20 W

EAN 4007841007751

**Version**

Neutral white

---

Indoor light

# RS PRO DL LED 20 W

EAN 4007841007751

Light distribution curve 1

Sensorenerfassungsbereich 1

