


Data sheet

Sensor-switched LED floodlight

XLED curved

V2 Anthracite

EAN 4007841012076



Function description

Illuminating compact model. Sensor LED floodlight XLED curved with 10 W, compact and discreet lighting solution for building entrances, pathways and co., attractive luminous efficiency (1125 lm) requiring very little energy, sensor reach of up to 8 m, tilting range of +30°.

Technical specifications

Dimensions (L x W x H)	120 x 160 x 107 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Mounting height max.	4,00 m
Sensor Technology	passive infrared
Output	10 W
Interconnection	No
Luminous flux	1125 lm
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	No

Data sheet

Sensor-switched LED floodlight

XLED curved

V2 Anthracite

EAN 4007841012076

Technical specifications

Reach, tangential r = 8 m (89 m²)

Photo-cell controller Yes

Twilight setting 2 – 1000 lx

Time setting 2 sec – 70 min

Basic light level function No

Soft light start No

Impact resistance IK00

IP rating IP44

Protection class II

Ambient temperature -20 – 50 °C

Housing material Plastic

Cover material Plastic, opal

Manufacturer's Warranty 3 years

PU1, net weight 0,390 kg

Version Anthracite

PU1, EAN 4007841012076

Mood image

