


Outdoor light

L 910 LED

EAN 4007841006570



Functional description

Same technology, even more effective: if you are looking for somewhat more ambient light on the outside of your home, we can offer you an uplighter/downlighter solution with the L 910 LED that's just as stylish as it is efficient. As with its little brother, no-maintenance and low-consumption LEDs give you aesthetically pleasing ambient lighting here too whenever you wish thanks to the reliable IR sensor. And if you interconnect them, they will also switch on and off simultaneously. An effect not only appreciated by admirers of aesthetic style.

Technical specifications

Dimensions (L x W x H)	235 x 80 x 85 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Output	11 W
Luminous flux	755 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	180 °
Sneak-by guard	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	r = 2 m (6 m ²) / r = 4 m (25 m ²)
Reach, tangential	r = 5 m (39 m ²) / r = 12 m (226 m ²)
Photo-cell controller	Yes
Twilight setting	2 – 20 lx
Time setting	120 s – 15 min
Basic light level function, detail	LED effect light
Soft light start	Yes
Continuous light	selectable, 4h
Impact resistance	IK00
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years https://www.steinel.de/

Data sheet



Outdoor light

L 910 LED

EAN 4007841006570

Version

white
