


Floodlight

XLED PRO 240

EAN 4007841003623



Functional description

The XLED PRO 240 sensor-switched outdoor floodlight is a lighting and detection wizard. The fully swivelling, extra-slim LED flat panel delivers 1830 lm of light, and is ideal for illuminating large areas around the building with on-demand lighting. In conjunction with 4000 K colour temperature, the opal diffuser produces an inviting lighting mood. The LED floodlight is fitted with a 240° infrared sensor that reliably detects the smallest of movements, has a reach of up to 12 m and makes an effective deterrent to unwanted visitors. With the adapter provided, fitting the light to a wall corner is not a problem. The LED floodlight has a power consumption of just 20 W.

Technical specifications

Dimensions (L x W x H)	221 x 180 x 161 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
max	6,00 m
Sensor Technology	passive infrared
Output	20 W
Luminous flux	1830 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	60000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	HCMC (High Conductive Magnesium Composite)
With motion detector	Yes
Detection angle	240 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	r = 12 m (302 m ²)
Photo-cell controller	Yes
Twilight setting	2 – 1000 lx
Time setting	10 s – 15 min
Impact resistance	IK00
IP rating	IP44
Protection class	II
Housing material	HCMC
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Includes corner wall mount	Yes
PU1, net weight	0,640 kg
Version	black

Data sheet



Floodlight

XLED PRO 240

EAN 4007841003623

Sensorenerfassungsbereich 1

Image not found or type unknown

