


## Floodlight

# XLED home 2 XL

EAN 4007841030063



## Functional description

The powerful XLED home 2 XL sensor-switched outdoor floodlight is the first choice for those who like it particularly bright or need to illuminate large areas. Innovative, highly efficient LEDs ensure the perfect illumination of driveways, courtyards and gardens. With an energy consumption of just . The XLED home 2 XL is also a moving wonder. The fully swivelling LED panel ensures maximum flexibility. In combination with the opal cover, the floodlight ensures optimum lighting conditions around the home with a colour temperature of 4000K. The XLED home 2 XL is available as an individual floodlight or as a slave version. Available in white, black, graphite and silver.

## Technical specifications

<b>Dimensions (L x W x H)</b>	214 x 180 x 161 mm
<b>Mains power supply</b>	230 – 240 V
<b>max</b>	4,00 m
<b>Sensor Technology</b>	passive infrared
<b>Luminous flux</b>	1608 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Drop in luminous flux in accordance with LM80</b>	L70B10
<b>LED cooling system</b>	HCMC (High Conductive Magnesium Composite)
<b>With motion detector</b>	Yes
<b>Detection angle</b>	140 °
<b>Sneak-by guard</b>	Yes
<b>Capability of masking out individual segments</b>	Yes
<b>Reach, tangential</b>	r = 14 m (239 m <sup>2</sup> )
<b>Photo-cell controller</b>	Yes
<b>Twilight setting</b>	2 – 2000 lx
<b>Time setting</b>	8 s – 35 min
<b>Basic light level function</b>	No
<b>Continuous light</b>	selectable
<b>Impact resistance</b>	IK00
<b>IP rating</b>	IP44
<b>Protection class</b>	II
<b>Ambient temperature</b>	-20 – 40 °C
<b>Housing material</b>	Plastic
<b>Cover material</b>	Plastic, opal
<b>Manufacturer's Warranty</b>	5 years
<b>PU1, net weight</b>	0,620 kg
<b>Version</b>	Silver