


Floodlight

XLED home 2 XL SL

EAN 4007841030087



Functional description

The powerful XLED home 2 XL sensor-switched outdoor floodlight is the first choice for those who like it particularly bright or need to illuminate large areas. Innovative, highly efficient LEDs ensure the perfect illumination of driveways, courtyards and gardens. With an energy consumption of just 20 W. The XLED home 2 XL is also a moving wonder. The fully swivelling LED panel ensures maximum flexibility. In combination with the opal cover, the floodlight ensures optimum lighting conditions around the home with a colour temperature of 4000K. The XLED home 2 XL is available as an individual floodlight or as a slave version. Available in white, black, graphite and silver.

Technical specifications

Dimensions (L x W x H)	199 x 180 x 161 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
max	4,00 m
Output	20 W
Luminous flux	1608 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	HCMC (High Conductive Magnesium Composite)
With motion detector	No
Photo-cell controller	No
Basic light level function	No
Continuous light	selectable
Impact resistance	IK00
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	HCMC
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
PU1, net weight	0,534 kg
Version	Silver