


Floodlight

XLED home 2 Z-Wave

EAN 4007841029838



Functional description

The moveable sensor-switched outdoor floodlight with fully swivelling LED panel in a classy opal look. The XLED home 2 Z-Wave sensor-switched floodlight comes in a sophisticated design. It is not just an eye-catcher, but also a truly talented mover. Thanks to the fully swivelling LED panel, every corner of the entrance area can be illuminated flexibly and as required. The highly efficient LED technology coupled with the opal cover provides maximum lighting comfort. As an individual floodlight or interconnected with the slave version, the innovative new generation of the XLED home success series is available in white, black, graphite and silver. Smart home included. The optional Smart Friends Box and the free Smart Friends app make it easy to set the XLED home 2 Z-Wave via smart phone or tablet. The floodlight can also be switched ON or OFF via app. Other Steinel products can also be interconnected. If you wish, this also works via remote control when you are out. That completes your own smart home building automation system. Along with STEINEL products, Smart Friends solutions from PAULMANN, SCHELLENBERG and ABUS can also be integrated. Smart homes from a brand-name provider.

Technical specifications

Dimensions (L x W x H)	194 x 180 x 161 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Output	14,8 W
Luminous flux	1184 lm
Colour temperature	4000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	HCMC (High Conductive Magnesium Composite)
With motion detector	Yes
Detection angle	140 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	r = 14 m (239 m ²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 min
Impact resistance	IK00
IP rating	IP44
Protection class	II
Transmitter range	Up to 100 m in the open, 30 m indoors
Housing material	HCMC
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
PU1, net weight	0,582 kg

<https://www.steinell.de/>

Data sheet



Floodlight

XLED home 2 Z-Wave

EAN 4007841029838

Version

Silver
