


## Floodlight

# XLED home 2 Z-Wave

EAN 4007841033996



## Functional description

The moveable sensor-switched outdoor floodlight with fully swivelling LED panel in a classy opal look. The XLED home 2 Z-Wave sensor-switched floodlight comes in a sophisticated design. It is not just an eye-catcher, but also a truly talented mover. Thanks to the fully swivelling LED panel, every corner of the entrance area can be illuminated flexibly and as required. The highly efficient LED technology coupled with the opal cover provides maximum lighting comfort. As an individual floodlight or interconnected with the slave version, the innovative new generation of the XLED home success series is available in white, black, graphite and silver. Smart home included. The optional Smart Friends Box and the free Smart Friends app make it easy to set the XLED home 2 Z-Wave via smart phone or tablet. The floodlight can also be switched ON or OFF via app. Other Steinel products can also be interconnected. If you wish, this also works via remote control when you are out. That completes your own smart home building automation system. Along with STEINEL products, Smart Friends solutions from PAULMANN, SCHELLENBERG and ABUS can also be integrated. Smart homes from a brand-name provider.

## Technical specifications

<b>Dimensions (L x W x H)</b>	194 x 180 x 161 mm
<b>Mains power supply</b>	230 – 240 V , 50 / 60 Hz
<b>Sensor Technology</b>	passive infrared
<b>Output</b>	14,8 W
<b>Luminous flux</b>	1184 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Drop in luminous flux in accordance with LM80</b>	L70B10
<b>LED cooling system</b>	HCMC (High Conductive Magnesium Composite)
<b>With motion detector</b>	Yes
<b>Detection angle</b>	140 °
<b>Sneak-by guard</b>	Yes
<b>Capability of masking out individual segments</b>	Yes
<b>Reach, tangential</b>	r = 14 m (239 m <sup>2</sup> )
<b>Photo-cell controller</b>	Yes
<b>Twilight setting</b>	2 – 2000 lx
<b>Time setting</b>	8 s – 35 min
<b>Impact resistance</b>	IK00
<b>IP rating</b>	IP44
<b>Protection class</b>	II
<b>Transmitter range</b>	Up to 100 m in the open, 30 m indoors
<b>Housing material</b>	HCMC
<b>Cover material</b>	Plastic, opal
<b>Manufacturer's Warranty</b>	5 years
<b>PU1, net weight</b>	0,480 kg

<https://www.steinell.de/>

Data sheet



Floodlight

# XLED home 2 Z-Wave

EAN 4007841033996

**Version**

graphite

---