


## Floodlight

# XLED PRO Wide SL

EAN 4007841010256



## Functional description

The new XLED PRO Wide floodlight. Lighting precision in wide format. Developed by STEINEL, the lens matrix and the fully swivelling and tilting flat design light head provides perfect illumination over particularly large areas or along buildings. The powerful high-end LEDs create an impressive brightness of 2400 lm while consuming just 24,8 W. The integrated basic light LEDs provide orientation and safety with minimal energy consumption. The sensor has an angle of coverage of 240° and a reach of 12 metres. The slave version offered separately can be interconnected simply via cable. If it has to be even brighter, night can be turned into day with the XLED PRO Wide XL version. Delivering 4400 lumens from just 48 watts, this spot light really ought to be called a floodlight.

## Technical specifications

<b>Dimensions (L x W x H)</b>	165 x 265 x 126 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>max</b>	6,00 m
<b>Output</b>	24,8 W
<b>Luminous flux</b>	2400 lm
<b>Colour temperature</b>	4000 K
<b>Colour variation LED</b>	SDCM3
<b>Colour Rendering Index CRI</b>	80-89
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>LED life expectancy (max. °C)</b>	50000 h
<b>Drop in luminous flux in accordance with LM80</b>	L70B10
<b>LED cooling system</b>	Passive Thermo Control
<b>With motion detector</b>	No
<b>Photo-cell controller</b>	No
<b>Twilight setting</b>	2 – 1000 lx
<b>Time setting</b>	5 s – 20 min
<b>Basic light level function time</b>	10 min, 30 min, all night
<b>Continuous light</b>	selectable, 4h
<b>Impact resistance</b>	IK00
<b>IP rating</b>	IP54
<b>Protection class</b>	I
<b>Ambient temperature</b>	-20 – 40 °C
<b>Housing material</b>	Aluminium
<b>Cover material</b>	Plastic, transparent
<b>Manufacturer's Warranty</b>	5 years
<b>PU1, net weight</b>	1,827 kg
<b>Version</b>	black