1060LM 25000H

Lamp range for basic use - pure white

Airam's PRO LED 3000 K series covers all light source needs for basic use. The lamps are in energy class A+ and have a long service life. This series includes the most common bulb types. The lamps are packed in cardboard boxes that clearly indicate the key technical specifications. Special characteristics for the lamps in this series include an extremely long operating life $(25,000\ h)$ and a high number of switch-on cycles (500,000). The colour temperature is pure white $(3000\ K)$

Opal classic LED lamp 10.5W 3000K E27 1060lm 25000h 60x110mm, cardboard packing. Supply frequency ~50/60Hz.

1060LM 25000H			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713432	A7PRAR	0.05	Pro



1060LM 25000H

EC001959

EC001959	
Mounting	
Structure	
Energy efficiency class	A+
Dimming and control	
With remote control	No
Remote operation possible	No
Photometric data	
Colour temperature (min) (K)	3000
Luminous flux (min) (lm)	1060
Colour rendering index CRI	80-89
Radiation angle (°)	220
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (max) (K)	3000
Luminous flux (max) (lm)	1060
Colour consistency (McAdam ellipse)	SDCM5
Photobiological safety according to EN 62471	RG0
Lifetime and capacity	
Measurements	
Length (mm)	110
Diameter (mm)	60
Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal current (min) (mA)	99
Nominal voltage (max) (V)	240
Nominal current (max) (mA)	99
Power factor	0.5

0.13

Energy Efficiency Index (EEI)

