

MODEL		KPSW 4
Type		2 pipes
Codes - Models with remote control		KPSW 4B5X
Features	Units	
Total cooling capacity (HS/MS/LS) ⁽¹⁾	kW	3,60/3,00/1,77
Sensible cooling capacity (HS/MS/LS) ⁽¹⁾	kW	3,06/2,50/1,48
Heating capacity (HS/MS/LS) ⁽²⁾	kW	5,30/4,30/2,40
Air flow rate (HS/MS/LS)	m ³ /h	675/570/330
Air flow rate (HS/MS/LS)	m ³ /s	0,188/0,158/0,092
Water flow in cooling mode (HS) ⁽¹⁾	l/h	617
Pressure drop in cooling mode (HS) ⁽¹⁾	kPa	25,8
Pressure drop in heating mode (HS) ⁽²⁾	kPa	23
Electricity supply	V/Ph/Hz	230/1/50
Total power consumption (HS)	kW	0,080
Total current (HS)	A	0,40
Hydraulic connection		1/2" G male
Sound power level (HS/MS/LS)	dB(A)	54/51/40
Sound pressure level (HS/MS/LS) at 2 m	dB(A)	46/43/32
Net dimension (H./W./D.)	mm	680x900x190
Net weight	kg	23,5

The pressure levels of Technibel products conform to European standard EN 12102

Nominal conditions

⁽¹⁾ T. Air inlet: +27°C D.B./ + 19°C W.B.

T. Water inlet: +7°C

T. Water outlet: +12°C

⁽²⁾ T. Air inlet: +20°C

T. Water inlet: +50°C (same water flow as in condition (1))

Max T. of water generated: +60°C