

MODEL		CHGF 55
Single pump code		CHG557F
Dual pump code		CHG557FB
Cooling capacity		
Power +7°C/+12°C / + 35°C ext.	kW	54,60
EER	kW/kW	2,98
Number of compressors		2
R410A refrigerant charge	kg	11,00
Circuit specifications and connections		
Expansion tank capacity	l	8
Nominal water flow rate (+7°C/35°C)	m ³ /h	9,4
Available head for pump	kPa	135
Storage tank capacity	l	125
Hydraulic connections	"	2" F
Electrical specifications and connections		
Power 50 Hz with GND		400 V + N
Startup current	A	117
Max current draw	A	48
Thermal cutout rating	A	63
Power cord cross section (1)		5G 25 mm ²
Running noise		
Sound power per EN12102	dB(A)	81
Sound pressure level at 10 m (2)	dB(A)	53
Limiti di funzionamento		
Air temperature range	°C	+47°C / -10°C
Water delivery temperature max./min.	°C	+16°C / +5°C (0°C with glycol)
Δ Exchanger water temperature, min./max.	°C	+3°C / +8°C
General specifications		
Dimensions H x L x D	mm	1735 x 2091 x 1183
Net weight	kg	657

- (1) Indicative data, must be checked against the installation conditions and legal requirements
(2) Sound pressure: unit outdoors on a reflective surface at a distance of 10m