

MATCHING		SKPF128L5
Indoor unit		KPAF128C5T
Outdoor unit		GRF128L5T
Features	Units	Cooling
Cooling capacity	kW	3,40
Energy label class	ABCDEFGH	A
E.E.R.	(kW/kW)	3,24
Air flowrate Indoor (h.-m.-l.)	m ³ /h	670-550-450
Dehumidification	l/h	1,5
Fan speeds (Indoor / Outdoor)	n°	3 + Auto/1
Sound pressure Indoor (h.-m.-l.)	dB(A)	47-44-39
Sound pressure Outdoor (h.)	dB(A)	40
Power supply	V/Ph/Hz	230/1/50
Power input	kW	1,05
Running consumption	A	4,70
Annual energy cons.- cooling mode (500h) - Directive 2002/31/CE	kWh	525
Compressor type		Rotary
Refrigerant type		R410A
Liquid pipe diameter	mm(inch")	6,35(1/4")
Gas pipe diameter	mm(inch")	12,7(1/2")
Max. pipe lenght with gas standard charge	m	7,5
Max. pipe lenght with gas additional charge	m	15
Gas additional charge	gr/m	20
Max. height between units (Outdoor on top)	m	7
Max. height between units (Indoor on top)	m	7
Net weight Indoor / Outdoor	Kg	23,5/34
Net dimension Indoor (H./W./D.)	mm	680x900x190
Net dimension Outdoor (H./W./D.)	mm	540x700x265

The technical data here indicated are in compliance with the European standard EN14511 - Directive 2002/31/EC