

MODEL		CWX 10
Type		2 pipes
Codes - Models without remote control		CWX 10B5B
Codes grille - Models without remote control		K70N095 T
Features	Units	
Total cooling capacity (HS/MS/LS) ⁽¹⁾	kW	9,92/8,09/6,23
Sensible cooling capacity (HS/MS/LS) ⁽¹⁾	kW	7,90/6,22/4,62
Heating capacity (HS/MS/LS) ⁽²⁾	kW	11,69/9,53/7,34
Air flow rate (HS/MS/LS)	m ³ /h	2300/1700/1200
Air flow rate (HS/MS/LS)	m ³ /s	0,631/0,472/0,339
Water flow rate in cooling mode (HS) ⁽¹⁾	l/h	1700
Pressure drop in cooling mode (HS) ⁽¹⁾	kPa	63
Pressure drop in heating mode (HS) ⁽²⁾	kPa	60
Electricity supply	V/Ph/Hz	230/1/50
Maximum power consumption (HS)	kW	0,180
Maximum total current (HS)	A	0,8
Hydraulic connection		3/4" G female
Sound power level (HS/MS/LS)	dBA	57/49/43
Sound pressure level (HS/MS/LS) at 2 m	dBA	48/40/34
Net dimension (H./W./D.)	mm	340x1050x1050
Net dimension grille (H./W./D.)	mm	48x860x860
Net weight unit + grille	kg	36

The pressure levels of Technibel products conform to European standard EN 12102

Nominal conditions

⁽¹⁾ T. Air inlet: +27°C D.B./ + 19°C W.B.

T. Water inlet: +7°C

T. Water outlet: +12°C

⁽²⁾ T. Air inlet: +20°C

T. Water inlet: +50°C / same water flow rate (1)