

MODEL		CWX 6
Type		2 pipes
Codes - Models without remote control		CWX 6B5B
Codes grille - Models without remote control		K70N094 T
Features	Units	
Total cooling capacity (HS/MS/LS) <sup>(1)</sup>	kW	6,00/5,00/4,20
Sensible cooling capacity (HS/MS/LS) <sup>(1)</sup>	kW	4,70/3,80/3,20
Heating capacity (HS/MS/LS) <sup>(2)</sup>	kW	7,70/6,40/5,40
Air flow rate (HS/MS/LS)	m <sup>3</sup> /h	1300/1060/850
Air flow rate (HS/MS/LS)	m <sup>3</sup> /s	0,361/0,294/0,233
Water flow rate in cooling mode (HS) <sup>(1)</sup>	l/h	1030
Pressure drop in cooling mode (HS) <sup>(1)</sup>	kPa	30
Pressure drop in heating mode (HS) <sup>(2)</sup>	kPa	27
Electricity supply	V/Ph/Hz	230/1/50
Maximum power consumption (HS)	kW	0,120
Maximum total current (HS)	A	0,5
Hydraulic connection		3/4" G female
Sound power level (HS/MS/LS)	dBA	51/44/40
Sound pressure level (HS/MS/LS) at 2 m	dBA	42/35/31
Net dimension (H./W./D.)	mm	310x760x760
Net dimension grille (H./W./D.)	mm	48x860x860
Net weight unit + grille	kg	28

The pressure levels of Technibel products conform to European standard EN 12102

Nominal conditions

<sup>(1)</sup> T. Air inlet: +27°C D.B./ + 19°C W.B.

T. Water inlet: +7°C

T. Water outlet: +12°C

<sup>(2)</sup> T. Air inlet: +20°C

T. Water inlet: +50°C / same water flow rate (1)