

## **Product information**

## 87 01 300 SB

## **KNIPEX Cobra®**

**DIN ISO 8976** 



- push the button for adjustment on the workpiece: fast and comfortable handling
- fine adjustment: ensures optimum adjustment to differently sized workpieces and user-friendly handle position
- reliable catching of the hinge bolt: no unintentional shifting
- · box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- gripping surfaces with special hardened teeth, teeth hardness approx.
  61 HRC: high wear resistance and stable gripping
- one-hand adjustment
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- Chrome vanadium electric steel, forged, multi stage oil-hardened

| Allgemein            |                  |  |
|----------------------|------------------|--|
| Article No.          | 87 01 300 SB     |  |
| EAN                  | 4003773014133    |  |
| weight               | 553 g            |  |
| Dimensions           | 300 x 84 x 87 mm |  |
| Technische Attribute |                  |  |
| Adjustment positions | 30               |  |

| Klassifikation                  |         |  |
|---------------------------------|---------|--|
| Capacities for pipes (diameter) | Ø 70 mm |  |
| Capacities for nuts             | 60 mm   |  |
| Capacities for nuts             | 2 3/4   |  |
| Adjustment positions            | 30      |  |

| Klassifikation |            |
|----------------|------------|
| eCl@ss 5.1.4   | 21040301   |
| ETIM 5.0       | EC000164   |
| ETIM 6.0       | EC000164   |
| proficl@ss 6.0 | AAA936c004 |

technical change and errors excepted