



SBO5.1

**Heat shrink breakout**

Code	SBO5.1
GTIN	6438100306618
ENumber	
Name	Heat shrink breakout 0.6/1 (1.2) kV Breakout 5 core diam.50/15
Description	The cable breakouts are used to protect the terminated cable ends against moisture and dirt. The breakouts are suitable for both plastic and belted paper insulated 1 kV cables. They are UV resistant and halogen free and with adhesive. The colour is black.

**Technical specification****Dimensions**

Conductor size:	5x6-70
Final wall thickness:	3.0 mm

**Drawing markings**

H:	105 mm
H1:	25 mm
D max/min:	50/15
D1 max/min:	15/4

**Ratings**

ETIM class:	EC002464
ETIM 7:	EC002464

**Cable Features**

No. of cores:	5
---------------	---

**ETIM****ETIM**

Diameter shaft before shrink:	50 mm
Type:	Heat-shrink

<b>Inner diameter finger before shrink:</b>	15 mm
<b>Inner diameter finger after shrink:</b>	4 mm
<b>Diameter shaft after shrink:</b>	15 mm
<b>Nominal cross section:</b>	6 ... 70 mm <sup>2</sup>
<b>Model:</b>	For 5-core cables
<b>Total length after shrink:</b>	105 mm

## Packaging

---

### Default package

<b>Size:</b>	100
<b>Length:</b>	220 mm
<b>Width:</b>	190 mm
<b>Height:</b>	43 mm
<b>Weight (brt):</b>	2.97 kg
<b>Volume:</b>	26.3465

### Pallet package

<b>Size:</b>	2400
<b>Length:</b>	1200 mm
<b>Width:</b>	800 mm
<b>Height:</b>	1030 mm
<b>Weight (brt):</b>	91.22 kg