

GENERAL CHARACTERISTICS

Modular surface-mounting containers for:

- Devices in the SYSTEM Range
- Push-buttons Ø 22 of the 74 PS range
- Modular devices for DIN rail mounting

IP 40 and IP 55 versions for installation in ordinary environments or external locations. The possibility of placing several containers alongside each other horizontally and laterally makes it possible to accomplish customized layouts that adapt in a versatile manner to a great number of different requirements. The range also includes complete devices and containers for gardens in the pole mounted and post bracket version.

REFERENCE STANDARDS AND TECHNICAL DATA

Products	Reference standards	IP Protection rating	Protection against indirect contacts	Installation temperature		Thermo-pressure with ball	Glow Wire Test
				Minimum	Maximum		
COMBI SYSTEM containers	CEI 23-48	IP 40 - IP 55	☐	-25°C	+60°C	70°C	650°C
COMBI 22 containers	EN 60670-22	IP 66	☐			70°C	650°C
Garden containers	IEC 60670-22	IP 55	☐			70°C	650°C
COMBI DIN containers	CEI 23-49 IEC 60670-24	IP 40	☐			70°C	650°C

* The standard references above concern the empty shells.

The shells supplied complete with devices meet the respective product norms.

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Agent	Water	Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
			Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistance*	Resistant	Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Resistant

* The resistance values given are valid for an ambient temperature not higher than 40°C.

CONSTRUCTION FEATURES

