



AD LINEAR L190 HIGH BAY

PRODUCT DATASHEET

Energy efficient luminaire with a long life span for high indoor locations. A wide range of customization options available.



TECHNICAL DATA

Overall information

Nominal power	189 W
Luminous flux	29 000 lm
Luminous efficacy	153 lm/W
Color temperature	5000 K (optional 4000 K and 3000 K)
CRI	> 80
Operating voltage	202...254 Vac
Mains frequency	47,5...63 Hz
Power factor λ	> 0.9
Operating temperature (Ta)	-40°C - +40°C
IP Rating	IP54
Protection class IK (shock resistance)	IK08
Surge Protection	DM 2kV, CM 4kV
Frame material	Recycled aluminium
Frame color	Anodized aluminium
Lighting control	ON/OFF, DALI (DALI-2)
Operating hours	> 50 000 hours
Guarantee	5 years
Country of origin	Finland

Dimensions (frame), weight & connection

Lenght	1792 mm
Width	86 mm
Height	77 mm
Weigth	6 kg
Type of connection	H05VV-F Cable, 3-pole / H05VV-F Cable, 5-pole (DALI)
Connection	Pre-installed 2m cable, through wiring optional, Phoenix/Enstonet/Wago Winsta/Wieland -connectors optional, cable lenght customizable

Mount

Mounting type	Installation brackets (2 pcs)
Mounting location	Rail, hang, ceiling
Mount	2 pcs M6 bolt

Light distribution patterns

