

ITY3-TW100LB

ITYS 10000VA VFI UPS 1/1 PF=1 +CHARGER

Compact tower UPS system saves space in the operating environment.



Strong points

- Robust and easy to install
- High protection and availability
- Certified product
- Wide battery configurability

General characteristics

- Embedded dry-contact interface.
- Input mains switch breaker.
- Connection for battery extension modules.
- Power off the UPS remotely.
- Internal temperature sensor.

Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- RCM (E2376)

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/ITY3-TW100LB>

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS 10000VA VFI UPS 1/1 PF=1 WITH POWERFUL CHARGER FOR EXTERNAL LONG AUTONOMY BATTERY , INTEGRATED MANUAL BYPASS
Effective date	2021-02-15
Country of origin	CN
Discount Policy	D05
Discount Policy Label	ITYS2
Weight	48.003

ETIM

Width	225
Height	354
Depth	416
Weight	15.8
Voltage type	AC
Suitable for network-management	Yes
Construction type	Free standing model
USB interface	Yes
Potential free switch contact	Yes
Input voltage	160..276
Output voltage	220..240
SNMP	Yes
USV- technology	Online
Primary frequency	40..70
Secondary frequency	50..60
Number of phases secondary	1
Number of phases primary	1
Auto shut down function	Yes
Max. voltage distortion output (linear load)	1
Output power factor	1
Overall efficiency	95
Efficiency in eco-mode	98
Input connection	Fixed connection
Number of output connections fixed connection	1
Output effective power	10000
Output apparent power	10000

Logistics

GTIN/EAN	8027122746038
Customs number	8504409590

Technical Characteristics

Depth	416
Height	354

In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	225
Sn	10
Pn	10
Conf	C1
Input voltage	230
Rate (min)	10
Rate (max)	10
Configuration	UPS Single Unit(s) with Bypass