



Table of content

MASTER LEDtube HF T5

• MASTER LEDtube HF InstantFit T5 HO - 1200 mm	2
• MASTER LEDtube HF InstantFit T5 HO - 1500 mm	3
• MASTER LEDtube HF InstantFit T5 UO - 1500 mm	5
• MASTER LEDtube HF InstantFit HE T5 - 600 mm	6
• MASTER LEDtube HF InstantFit HE T5 - 900 mm	7
• MASTER LEDtube HF InstantFit HE T5 - 1200 mm	8
• MASTER LEDtube HF InstantFit HE T5 - 1500 mm	9

MASTER LEDtube HF T8

• MASTER LEDtube HF InstantFit T8 - 600 mm	10
• MASTER LEDtube HF InstantFit T8 - 1200 mm	12
• MASTER LEDtube HF InstantFit T8 - 1500 mm	14
• MASTER LEDtube Universal T8 - 1200 mm	16
• MASTER LEDtube Universal T8 - 1500 mm	18

MASTER Value LEDtube Universal T8

• MASTER Value LEDtube Universal T8 - 1200 mm	20
• MASTER Value LEDtube Universal T8 - 1500 mm	22

CorePro LEDtube HF T8

• CorePro LEDtube HF InstantFit T8 - 600 mm	24
• CorePro LEDtube HF InstantFit T8 - 1200 mm	25
• CorePro LEDtube HF InstantFit T8 - 1500 mm	27
• CorePro LEDtube Universal HO - 1200 mm	29
• CorePro LEDtube Universal HO - 1500 mm	31

MASTER LEDtube HF InstantFit HE T5 - 900 mm




Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



MAS LEDtube HF 900mm
HE 11W 8xx T5

Model number / EOC code:
9290019957 / 871869963281600
9290019958 / 871869963283000
9290019959 / 871869963285400

AC (50 Hz) on HF Ballast Compatible

	Ballast type	12nc	Lamps on ballast
PHILIPS	HF-P 1 14-35 TL5 HE III IDC 4CIC	9137130310	1
	HF-P 1 14-35 TL5 HE III IDC C2E	9137130310	1
	HF-P 2 14-35 TL5 HE III IDC	9137130311	2
	HF-S 114-35 TL5 II	9137130429	1
	HF-S 2 14-35 TL5 HE II	9137130421	2
OSRAM	QT-FIT5 1x14-35		1
	QT-FIT5 2x14-35		2
	QTP5 1x14-35		1
	QTP5 2x14-35		2
HELVAR	EL1x14-35ngn5		1
TRIDONIC ATCO	PC 1x14-35 T5 PRO lp	22185147	1
	PC 1x14-35 T5 TOP lp	22185157	1
	PC 2x14-28 T5 TOP lp	22185158	2
VOSSLOH- SCHWABE			
BAG- HUECO			
Others	Direct Mains		1

General note Philips Master LEDtube HF InstantFit HE T5

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes InstantFit T5 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T5 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LEDtubes InstantFit T5 range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit HE T5 - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	12nc	Lamps on ballast
PHILIPS	EB-C 128 TL5	9137131964	1
	EB-C 228 TL5	9137131971	2
	EB-Ci 1-2 14-28W	9137130432	1
	EB-Ci 1-2 14-28W	9137130432	2
	HF-P 1 14-35 TL5 HE III IDC	9137130310	1
	HF-P 2 14-35 TL5 HE III IDC	9137130311	2
	HF-S 2 14-35 TL5 HE II	9137130421	2
	HF-R Es 114-35 TL5	9137006616	1
	HF-R Es 214-35 TL5	9137006617	2
	HF-R T 228 TL5 220-240	9137001863	2
	HF-Ri TD 2 28/35/49/54 TL5 E+ 195-240V	9137006958	2
OSRAM	QT-FIT5 1x14-35		1
	QT-FIT5 2x14-35		2
	QTP5 1x14-35		1
	QTP5 2x14-35		2
	EZ-T5 1x28/220		1
	EZP5 1x28/220-230		1
	EZP5 2x28/220-230		2
HELVAR	EL1x14-35ngn5		1
	EL1x14-35ngn5		2
TRIDONIC ATCO	PC 1x14-35 T5 TOP Ip	22185157	1
	PC 2x14-28 T5 TOP Ip	22185158	2
	PC 1x14-35 T5 PRO Ip	22185147	1
	PC 2x14-35 T5 PRO Ip	22185148	2
VOSSLOH-SCHWABE	ELXc 135.220	188921	1
BAG-HUECO	BCS35.1FX-11/220-240	10077579	1
Others	Direct mains		

MAS LEDtube HF 1200mm HE 16.5W 8xx T5
Model number / EOC code: 9290013910 / 871869674329400 9290013911 / 871869674331700 9290013912 / 871869674333100
AC (50 Hz) on HF Ballast Compatible
*
*
*
Dim
Dim
Dim
*
*
*
-1
*
*
*

General note Philips Master LEDtube HF InstantFit HE T5

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes InstantFit T5 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T5 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LEDtubes InstantFit T5 range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit HE T5 - 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	12nc	Lamps on ballast
PHILIPS	HF-P 1 14-35 TL5 HE III IDC	9137130310	1
	HF-P 2 14-35 TL5 HE III IDC	9137130311	2
	HF-S 2 14-35 TL5 HE II	9137130421	2
	HF-R Es 114-35 TL5	9137006616	1
	HF-R Es 214-35 TL5	9137006617	2
	HF-P 135 TLD 220-240	9137001367	1
	HF-Ri TD 2 28/35/49/54 TL5 E+ 195-240V	9137006958	2
OSRAM	QT-FIT5 1x14-35		1
	QT-FIT5 2x14-35		2
	QTP5 1x14-35		1
	QTP5 2x14-35		2
HELVAR	EL1x14-35ngn5		1
TRIDONIC ATCO	PC 1x14-35 T5 TOP Ip	22185157	1
	PC 2x35 T5 TOP Ip	28000047	2
	PC 1x14-35 T5 PRO Ip (production date before 2014)	22185147	1
	PC 1x14-35 T5 PRO Ip (production date after 2014)	22185147	1
	PC 2x14-35 T5 PRO Ip	22185148	2
VOSSLÖH-SCHWABE	ELXc 135.220	188921	1
BAG-HUECO	BCS35.1FX-11/220-240	10077579	1
Others	Direct mains		

MAS LEDtube HF 1500mm HE 20W 8xx T5
Model number / EOC code: 9290013913 / 871869674335500 9290013914 / 871869674337900 9290013915 / 871869674339300
AC (50 Hz) on HF Ballast Compatible
Dim
Dim
*

General note Philips Master LEDtube HF InstantFit HE T5

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes InstantFit T5 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T5 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LEDtubes InstantFit T5 range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit T8 - 600 mm



Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



MASTER LEDtube HF, Instant Fit 600mm HF 1050lm
Model number / EOC code: 9290013931A / 871869674353900 9290013932A / 871869674355300 9290013933A / 871869674367600
AC (50Hz) on HF Ballast Compatible

	Ballast type	10nc / Ref. no.	Lamps on ballast
TRIDONIC ATCO	PC 118 PRO Ip	22185213	1
	PC 218 PRO Ip	22185216	2
	PC 1X18-24W BASIC	22176000	1
	PC 1x18 T8 TOP sl	22185222	1
	PC 3/4X18 TOP Ip	22185219 / 22185228	3
	PC 3/4X18 TOP Ip	22185219 / 22185228	4
	PC 1/14-35/24/39 T5 PRO-M Ip	22176182	1
	PC 2/14-35/24/39 T5 PRO-M Ip	22176185	2
	PC 1x18 T8 TEC	87500113	1
	PC 2x18 T8 TEC	87500114	2
	PC 2x36 T8 TEC (4x18 T8 TEC)	87500116	4
VOSSLÖH-SCHWABE	ELXc 136.200	188314	1
	ELXc 236.208		2
	ELXc 424.379	188116	3
	ELXc 424.379	188116	4
	ELXc 418.204	188318	3
	ELXc 418.204	188318	4
	ELXc 136.207		1
BAG-HUECO	BCS18.1FX-11/220-240	1007 7588	1
	BCS18.2FX-11/220-240	1007 7589	2
	BCS18.3-4LR-01/220-240 3lamp	1005 0999	3
	BCS18.3-4LR-01/220-240 4lamp	1005 0999	4
Others	Direct mains		
	Electro Magnetic Ballast		

*	
*	
*	
*	
*	
*	
*	

General note Philips Master LEDtube HF InstantFit T8

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Philips 600mm MASTER LEDtubes InstantFit T8 are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit T8 - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast	MASTER LEDtube HF 1200mm 16.5W 833 T8 MEAT	MASTER LEDtube 1200mm HF HO, InstantFit 2100lm	MASTER LEDtube 1200mm HF UO, InstantFit 2500lm
				Model number / EOC code: 9290012263 / 871869656616900	Model number / EOC code: 9290012843A/B / 871869668752900 9290012841A/B / 871869668748200 9290012842A/B / 871869668750500	Model number / EOC code: 9290013002A/B / 871869668800700 9290013000A/B / 871869668796300 9290013001A/B / 871869668798700
				AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible
PHILIPS	EB-C 136 TL-D 220-240	9137131992	1			
	HF-B 136 TLD 220-240	9137001122	1			
	HF-B 136 TLD EII 220-240	9137001926	1			
	HF-B 236 TL-D 220-240	9137001124	2			
	HF-B 236 TLD EII 220-240	9137001928	2			
	HF-E 136 TL-D II	9137130410	1			
	HF-E 236 TL-D	9137130391	2			
	HF-E 236 TL-D II	9137130411	2			
	HF-K 136 TLD 220-240	9137001477	1			
	HF-P 136 TL-D III IDC	9137130315	1			
	HF-P 236 TL-D III IDC	9137130316	2			
	HF-P 336 TL-D III IDC	9137130317	3			
	HF-P Xt 136 TLD EII 220-240	9137006177	1			
	HF-P XT 236 TLD EII 220-240	9137006178	2			
	HF-P 136 TLD EII 220-240	9137001911	1			
	HF-P 236 TLD 230-240	9137001112	2			
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	9137006240	1			
	HF-R 136 TL-D EII	9137006092	1			
	HF-R 236 TL-D EII	9137006093	2			
	HF-R 136 TL-D 220-240V 50/60Hz	9137001117	1			
	HF-Ri TD 1 14/21/24/39TL5 E+	9137006983	1			
	HF-Ri TD 2 14/21/24/39TL5 E+	9137006984	2			
	HF-S 136 TL-D II	9137130321	1			
HF-S 236 TL-D II	9137130324	2				
HF-S 336 TL-D II	9137130327	3				
HF-P 118/136 TL-D III	9137130315	1				
HF-S 118/136 TL-D II	9137130321	1				
HF-P 218/236 TL-D III	9137130316	2				
HF-S 218/236 TL-D II	9137130324	2				
OSRAM	QT-FIT8 1x36		1			
	QT-FIT8 2x36		2			
	QTP8 1x36		1			
	QTP8 2x36		2			
	QTP-OPTIMAL 1x18-40		1			
	QTP-OPTIMAL 2x18-40		2			
	QT-FIT 5/8 2x18-39		2			
HELVAR	EL1x36/40/18S		1			
	EL1x36HF		1			
	EL1x36ngn		1			
	EL2x36/40s		2			
	EL2x36ngn		2			

MASTER LEDtube HF InstantFit T8 - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast	MASTER LEDtube HF 1200mm 16.5W 833 T8 MEAT	MASTER LEDtube 1200mm HF HO, InstantFit 2100lm	MASTER LEDtube 1200mm HF UO, InstantFit 2500lm
				Model number / EOC code: 9290012263 / 871869656616900	Model number / EOC code: 9290012843A/B / 871869668752900 9290012841A/B / 871869668748200 9290012842A/B / 871869668750500	Model number / EOC code: 9290013002A/B / 871869668800700 9290013000A/B / 871869668796300 9290013001A/B / 871869668798700
				AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible
TRIDONIC ATCO	PC 1/36 T8 INDUSTRY	86458035	1			
	PC 1/36 T8 PRO	22176217	1			
	PC 1x36 T8 PRO lp	22185214	1			
	PC2/36 T8 INDUSTRY	86458036	2			
	PC2x36 T8 PRO sl	22185217	2			
	PC 2x36 T8 TOP sl	22185226	2			
	PC 1x36 T8 TOP sl	22185223	1			
	PC1/36 T8 PRO sc	89800008	1			
	PC 1/36 T8 PRO	22176108	1			
	PC 3/36 T8 PRO	22176231	3			
VOSSLOH-SCHWABE	ELXc 136.207	188708	1			
	ELXc 236.202	188316	2			
	ELXc 236.208	188705	2			
	ELXe 238.527	188137	2			
	ELXe 238.527	188137	1			
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1			
	BCS36.2FX-11/220-240	10077591	2			
	D36.2-23021 E	166132	2			
	D 58.1-23021 E	166072	1			
	ECS36.2SR-01/220-240	167032	2			
Trilux	D36.2-23021 E		2			
	D58.1-23021E		1			
	DD58.1-23031E		1			
Others	EM ballast		1			
	Direct Mains		1			

General note Philips Master LEDtube HF InstantFit T8

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit T8 - 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



			MASTER LEDtube 1500mm HF HO, InstantFit 3100lm	MASTER LEDtube 1500mm HF UO, InstantFit 3700lm	
			Model number / EOC code: 9290012846A/B / 871869668758100 9290012844A/B / 871869668754300 9290012845A/B / 871869668756700	Model number / EOC code: 9290013005A/B / 871869668806900 9290013003A/B / 871869668802100 9290013004A/B / 871869668804500	
			AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible	
Ballast type	10nc / Ref. no.	Lamps on ballast			
PHILIPS	EI 158 TL-D 220-240	9137 006 075	1		*
	HF-B 158 TLD 220-240	9137 001 123	1		*
	HF-B 158 TLD EII 220-240	9137 001 927	1	*	*
	HF-B 258 TLD 220-240	9137 001 125	2	*	*
	HF-B 258 TL-D EII 220-240	9137 001 929	2	*	*
	HF-E 158 TL-D	9137 130 389	1		*
	HF-E 1/2 58 TL-D II	9137 130 409	2		*
	HF-E 1/2 58 TL-D II	9137 130 409	1	*	*
	HF-P 154/155 TL5 HO/PL-L III IDC	9137 130 282	1		*
	HF-P 158 TLD EII 220-240	9137 001 912	1	*	*
	HF-P 158 TL-D III IDC	9137 130 318	1		*
	HF-P 258 TLD EII 220-240	9137 001 916	2	*	*
	HF-P 258 TL-D III IDC	9137 130 319	2		*
	HF-P Xt 158 TLD EII 220-240	9137 006 179	1	*	*
	HF-P Xt 258 TL-D EII 220-240	9137 006 180	2	*	*
	HF-P 158 TLD 220-240	9137 001 185	1		*
	HF-P 258 TLD 220-240	9137 001 110	2	*	*
	HF-R 258 TLD 220-240	9137 001 119	2	Dim/**	Dim
	HF-R 158 TLD EII	9137 006 094	1	Dim	Dim
	HF-R 258 TLD EII	9137 006 095	2		
	HF-RITD 1 28/35/49/54TL5 E+	9137006956	1		
	HF-RITD 2 28/35/49/54TL5 E+	9137006958	2		
	HF-S 158		1	*	*
	HF-S 158 TL-D II	9137 130 322	1		*
	HF-S 258 TL-D II	9137 130 325	2		*
	HF-S 258 TL-D II HT	9137 006 899	2		*
	HF-S 158 TLD 220-240	9137 006 319	1		*
	EB-P 258 TLD ICC 220-240	9137 130 210	2	*	*
HF-P 258 TLD 220-240	9137001206	2			
OSRAM	QT Deluxe HF 1x58 230-240 DIM				
	QT Deluxe HF 2x58 230-240 Dim				
	QT-FIT8 1x58 - 70		1		
	QT-FIT8 2x58 70		2		
	QTP8 1x58		1	*	*
	QTP8 2x58		2	*	*
	QTP-OPTIMAL 1x54-58		1		*
	QTP OPTIMAL 2x54 58		2		*
	QT 1X58 DIM		1		*
	QT-FIT 5/8 1x54-58		1		*
	QT-FIT 5/8 2x54-58		2		*
	QT-FIT8 2x58		2		*
HELVAR	EL1x58ngn		1		
	EL1x58s		1		
	EL2x58es		2	*	*
	EL2x58HF		2		*
	EL2x58ngn		2		*
	EL2x58s		2		*
TRIDONIC ATCO	PC 1/58 T8 INDUSTRY	86 458 037	1	*	*
	PC 1/58 T8 PRO	22 176 094	1	*	*
	PC 1x58 T8 PRO Ip	22 185 215	1	*	*
	PC 2/58 T8 INDUSTRY	86 458 038	2	*	*
	PC 2x58 E011		2	*	*
	PC 2x58 E011 IDC	22 083 174	2		*
	PC 2x58 T8 PRO sl	22 185 218	2	*	*
	PC 1x58 T8 TOP sl	22185224	1		*
	PC 2x58 T8 TOP sl	22185227	2	*	*
	PCA 1/58 excel one4all	22 085 286	1		*
	PCA 2x58 EXCEL One4all Ip	28 000 040	2		*

MASTER LEDtube HF InstantFit T8 - 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



			MASTER LEDtube 1500mm HF HO, InstantFit 3100lm	MASTER LEDtube 1500mm HF UO, InstantFit 3700lm
			Model number / EOC code: 9290012846A/B / 871869668758100 9290012844A/B / 871869668754300 9290012845A/B / 871869668756700 AC (50 Hz) on HF Ballast Compatible	Model number / EOC code: 9290013005A/B / 871869668806900 9290013003A/B / 871869668802100 9290013004A/B / 871869668804500 AC (50 Hz) on HF Ballast Compatible
Ballast type	10nc / Ref. no.	Lamps on ballast		
VOSSLOH-SCHWABE	ELXc 158.201	188315	1	
	ELXc 158.209	188706	1	
	ELXc 158.218	188870	1	
	ELXc 258.203	188317	2	
	ELXc 258.210	188707	2	
	ELXc 258.219	188871	2	
	ELXe 258.222	188130	2	
	ELXe 158.524	188024	1	
BAG-HUECO	BCD58.1F-01/220-240/1-10V	1009 7145	1	Dim / *
	BCS58.1FX-11/220-240	1007 7592	1	
	BCS58.2FX-11/220-240	1007 7593	2	
	BCS58.2SX-01/220-240	1005 1003	2	
	D 58.1-23021 E	166 072	1	
	D 58.2-23021 E	166 082	2	
Trilux	DD58.1-23031E		1	
	DD58.1-23031E		1	
May + Christite	MCU 158		1	
	MCU 258		2	
Others	Direct mains			
	Electro Magnetic Ballast			

General note Philips Master LEDtube HF InstantFit T8

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube Universal T8 - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible
	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
	ELXe 238.527	188137	1
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Trilux	D36.2-23021 E		2
	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains (only one single side supply)		1

MASTER LEDtube 1200mm Universal, Instant Fit 2500lm
Model number / EOC code: 9290013361 / 871869670537700 9290013362 / 871869670539100 9290013360 / 871869672853600
AC (50Hz) on HF Ballast Compatible

General note Philips Master LEDtube Universal T8

General notes: Philips LEDtubes Universal T8 are designed to work on HF ballasts, or EM ballast, or direct mains connection.

For HF ballast connection: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes Universal T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes Universal T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with HF ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

For EM ballasts or direct mains connection: Please refer to the installation guide.

MASTER LEDtube Value UN - 1200mm



Ballast Compatibility

KEY

	Ballast is compatible
•	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



MAS LEDtube VLE UN 1200mm UO 16W8xx T8 2500lm
Product reference number: 9290023330 / 871869973917100 9290023331 / 871869973919500 9290023332 / 871869973921800

	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
	ELXe 238.527	188137	1
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Trilux	D36.2-23021 E		2
	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains		1

AC (50Hz) on HF Ballast Compatible
•
•
•
•
•

General note Philips MASTER Value LEDtube Universal HO

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp.

All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube VLE UN T8 – 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
•	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



MAS LEDtube VLE UN
1500mm UO 24W8xx T8
3700lm

Product reference number:
9290023333 / 871869973923200
9290023334 / 871869973925600
9290023335 / 871869973927000

	Ballast type	10nc / Ref. no.	Lamps on ballast	Compatibility
PHILIPS	HF-B 158 TLD 220-240	9137 001 123	1	Compatible
	HF-B 158 TLD EII 220-240	9137 001 927	1	Compatible
	HF-B 258 TLD 220-240	9137 001 125	2	Compatible
	HF-B 258 TL-D EII 220-240	9137 001 929	2	Compatible
	HF-E 158 TL-D	9137 130 389	1	Compatible
	HF-E 1/2 58 TL-D II	9137 130 409	2	Compatible
	HF-E 1/2 58 TL-D II	9137 130 409	1	Compatible
	HF-P 154/155 TL5 HO/PL-L III IDC	9137 130 282	1	Compatible
	HF-P 158 TLD EII 220-240	9137 001 912	1	Compatible
	HF-P 158 TL-D III IDC	9137 130 318	1	Compatible
	HF-P 258 TLD EII 220-240	9137 001 916	2	Compatible
	HF-P 258 TL-D III IDC	9137 130 319	2	Compatible
	HF-P Xt 158 TLD EII 220-240	9137 006 179	1	Compatible
	HF-P Xt 258 TL-D EII 220-240	9137 006 180	2	Compatible
	HF-P 158 TLD 220-240	9137 001 185	1	Compatible
	HF-P 258 TLD 220-240	9137 001 110	2	Compatible
	HF-R 258 TLD 220-240	9137 001 119	2	Compatible
	HF-R 158 TLD EII	9137 006 094	1	Compatible
	HF-R 258 TLD EII	9137 006 095	2	Compatible
	HF-RiTD 1 28/35/49/54TL5 E+	9137006956	1	Compatible
	HF-RiTD 2 28/35/49/54TL5 E+	9137006958	2	Compatible
	HF-S 158		1	Compatible
	HF-S 158 TL-D II	9137 130 322	1	Compatible
	HF-S 158 TL-D II 220-240V 50/60Hz	9137 130 322	1	Compatible
	HF-S 258 TL-D II	9137 130 325	2	Compatible
HF-S 258 TL-D II HT	9137 006 899	2	Compatible	
HF-S 158 TLD 220-240	9137 006 319	1	Compatible	
EB-P 258 TLD ICC 220-240	9137 130 210	2	Compatible	
HF-P 258 TLD 220-240	9137001206	2	Compatible	
OSRAM	QT Deluxe HF 1x58 230-240 DIM		1	Compatible
	QT Deluxe HF 2x58 230-240 Dim		2	Compatible
	QT-FIT8 1x58 - 70		1	Compatible
	QT-FIT8 2x58 70		2	Compatible
	QTP8 1x58		1	Compatible
	QTP8 2x58		2	Compatible
	QTP-OPTIMAL 1x54-58		1	Compatible
	QTP OPTIMAL 2x54 58		2	Compatible
	QT 1X58 DIM		1	Compatible
	QT-FIT 5/8 1x54-58		1	Compatible
	QT-FIT 5/8 2x54-58		2	Compatible
	QT-FIT8 2x58		2	Compatible
HELVAR	EL1x58ngn		1	Compatible
	EL1x58s		1	Compatible
	EL2x58es		2	Compatible
	EL2x58HF		2	Compatible
	EL2x58ngn		2	Compatible
	EL2x58s		2	Compatible
TRIDONIC ATCO	PC 1/58 T8 INDUSTRY	86 458 037	1	Compatible
	PC 1/58 T8 PRO	22 176 094	1	Compatible
	PC 1x58 T8 PRO Ip	22 185 215	1	Compatible
	PC 2/58 T8 INDUSTRY	86 458 038	2	Compatible
	PC 2x58 E011 IDC	22 083 174	2	Compatible
	PC 2x58 T8 PRO sl	22 185 218	2	Compatible
	PC 1x58 T8 TOP sl	22185224	1	Compatible
	PC 2x58 T8 TOP sl	22185227	2	Compatible
	PCA 1/58 excel one4all	22 085 286	1	Compatible
	PCA 2x58 EXCEL One4all Ip	28 000 040	2	Compatible

MASTER Value Universal - 1500mm

Ballast Compatibility



KEY

	Ballast is compatible
•	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



MAS LEDtube VLE UN
1500mm UO 24W8xx T8
3700lm

Product reference number:
9290023333 / 871869973923200
9290023334 / 871869973925600
9290023335 / 871869973927000

AC (50Hz) on HF Ballast Compatible

	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 158.201	188315	1
	ELXc 158.209	188706	1
	ELXc 258.203	188317	2
	ELXc 258.210	188707	2
	ELXc 258.219	188871	2
	ELXe 258.222	188130	2
	ELXe 258.222	188130	1
	ELXe 158.524	188024	1
BAG-HUECO	BCD58.1F-01/220-240/1-10V	1009 7145	1
	BCS58.1FX-11/220-240	1007 7592	1
	BCS58.2FX-11/220-240	1007 7593	2
	BCS58.2SX-01/220-240	1005 1003	2
	D 58.1-23021 E	166 072	1
	D 58.2-23021 E	166 082	2
Trilux	D58.1-23021E		1
	DD58.1-23031E		1
May + Christie	MCU 158		1
	MCU 258		2
Others	Direct mains		
	Electro Magnetic Ballast		

General note Philips MASTER Value LEDtube Universal HO

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp.

All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

CorePro LEDtube HF InstantFit T8 - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible
	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



Corepro LEDtube HF, Instant Fit 1200mm 1600lm
Model number / EOC code : 9290012499 / 871869658127800 9290011365 / 871869658129200
AC (50Hz) on HF Ballast Compatible

	Ballast type	10nc / Ref. no.	Lamps on ballast	
PHILIPS	EB-C 136 TL-D 220-240	9137131992	1	
	EB-S 236 TL-D 220-230	9137130216	2	
	HF-B 136 TLD 220-240	9137001122	1	
	HF-B 136 TLD EII 220-240	9137001926	1	
	HF-B 236 TL-D 220-240	9137001124	2	
	HF-B 236 TLD EII 220-240	9137001928	2	
	HF-E 136 TL-D II	9137130410	1	
	HF-E 236 TL-D	9137130391	2	
	HF-E 236 TL-D II	9137130411	2	
	HF-K 136 TLD 220-240	9137001477	1	
	HF-P 136 TL-D III IDC	9137130315	1	
	HF-P 236 TL-D III IDC	9137130316	2	
	HF-P 336 TL-D III IDC	9137130317	3	
	HF-P Xt 136 TLD EII 220-240	9137006177	1	
	HF-P XT 236 TLD EII 220-240	9137006178	2	
	HF-P 136 TLD EII 220-240	9137001911	1	
	HF-P 236 TLD 230-240	9137001112	2	
	HF-Pi 1 14/21/24/28/39 TL5 EII 220-240	9137006240	1	
	HF-R 136 TL-D EII 220-240V 50/60Hz	9137006092	1	
	HF-R 236 TL-D EII 220-240V 50/60Hz	9137006093	2	
	HF-R 136 TL-D 220-240V 50/60Hz	9137001117	1	
	HF-R 236 TL-D 220-240V 50/60Hz	9137001120	2	
	HF-S 136 TL-D II	9137130321	1	
	HF-S 236 TL-D II	9137130324	2	
	HF-S 336 TL-D II	9137130327	3	
	HF-P 118/136 TL-D III	9137130315	1	
	HF-S 118/136 TL-D II	9137130321	1	
	HF-P 218/236 TL-D III	9137130316	2	
	HF-S 218/236 TL-D II	9137130324	2	
	OSRAM	QT-FIT8 1x36		1
QT-FIT8 2x36			2	
QTP8 1x36			1	
QTP8 2x36			2	
QTP-OPTIMAL 1x18-40			1	
QTP-OPTIMAL 2x18-40			2	
QT-FIT 5/8 2x18-39			2	
HELVAR	EL1x36/40/18S		1	
	EL1x36HF		1	
	EL1x36ngn		1	
	EL2x36/40s		2	
	EL2x36ngn		2	
TRIDONIC ATCO	PC 1/36 T8 INDUSTRY	86458035	1	
	PC 1/36 T8 PRO	22176217	1	
	PC 1x36 T8 PRO lp	22185214	1	
	PC2/36 T8 INDUSTRY	86458036	2	
	PC2x36 T8 PRO sl	22185217	2	
	PC 2x36 T8 TOP sl	22185226	2	
	PC 1x36 T8 TOP sl	22185223	1	
	PC1/36 T8 PRO sc	89800008	1	
	PC 1/36 T8 PRO	22176108	1	
	PC 3/36 T8 PRO	22176231	3	



CorePro LEDtube HF InstantFit T8 - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible	This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions
•	Ballast is compatible, light output may differ >10% compared to specifications	
	Ballast is not compatible	



Corepro LEDtube HF, Instant Fit 1200mm 1600lm
Model number / EOC code : 9290012499 / 871869658127800 9290011365 / 871869658129200
AC (50Hz) on HF Ballast Compatible

	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Trilux	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains		1

General note Philips CorePro LEDtube HF InstantFit T8

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes are only tested with HF ballast on AC operation. The performance of Philips LEDtubes on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Philips CorePro LEDtubes HF InstantFit T8 are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

CorePro LEDtube HF InstantFit T8 - 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
•	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



Ballast type	10nc / Ref. no.	Lamps on ballast
PHILIPS EI 158 TL-D 220-240	9137 006 075	1
PHILIPS HF-B 158 TLD 220-240	9137 001 123	1
PHILIPS HF-B 158 TLD EII 220-240	9137 001 927	1
PHILIPS HF-B 258 TLD 220-240	9137 001 125	2
PHILIPS HF-B 258 TL-D EII 220-240	9137 001 929	2
PHILIPS HF-E 158 TL-D	9137 130 389	1
PHILIPS HF-E 1/2 58 TL-D II	9137 130 409	2
PHILIPS HF-E 1/2 58 TL-D II	9137 130 409	1
PHILIPS HF-P 158 TLD EII 220-240	9137 001 912	1
PHILIPS HF-P 158 TL-D III IDC	9137 130 318	1
PHILIPS HF-P 258 TLD EII 220-240	9137 001 916	2
PHILIPS HF-P 258 TL-D III IDC	9137 130 319	2
PHILIPS HF-P Xt 158 TLD EII 220-240	9137 006 179	1
PHILIPS HF-P Xt 258 TL-D EII 220-240	9137 006 180	2
PHILIPS HF-P 258 TLD 220-240	9137 001 110	2
PHILIPS HF-S 158		1
PHILIPS HF-S 158 TL-D II	9137 130 322	1
PHILIPS HF-S 258 TL-D II	9137 130 325	2
PHILIPS HF-S 258 TL-D II HT	9137 006 899	2
PHILIPS HF-S 158 TLD 220-240	9137 006 319	1
PHILIPS EB-P 258 TLD ICC 220-240		2
OSRAM QT-FIT8 1x58-70		1
OSRAM QT-FIT8 2x58-70		2
OSRAM QTP8 1x58		1
OSRAM QTP8 2x58		2
OSRAM QTP-OPTIMAL 1x54-58		1
OSRAM QTP OPTIMAL 2x54 58		2
OSRAM QT-FIT 5/8 1x54-58		1
OSRAM QT-FIT 5/8 2x54-58		2
HELVAR EL1x58ngn		1
HELVAR EL1x58s		1
HELVAR EL2x58es		2
HELVAR EL2x58HF		2
HELVAR EL2x58ngn		2
HELVAR EL2x58s		2
TRIDONIC ATCO PC 1/58 T8 INDUSTRY	86 458 037	1
TRIDONIC ATCO PC 1/58 T8 PRO	22 176 094	1
TRIDONIC ATCO PC 1x58 T8 PRO Ip	22 185 215	1
TRIDONIC ATCO PC 2/58 T8 INDUSTRY	86 458 038	2
TRIDONIC ATCO PC 2x58 E011		2
TRIDONIC ATCO PC 2x58 E011 IDC	22 083 174	2
TRIDONIC ATCO PC 2x58 T8 PRO sl	22 185 218	2
TRIDONIC ATCO PC 1x58 T8 TOP sl	22185224	1
TRIDONIC ATCO PC 2x58 T8 TOP sl	22185227	2
TRIDONIC ATCO PCA 1/58 excel one4all	22 085 286	1
TRIDONIC ATCO PCA 2x58 EXCEL One4all Ip	28 000 040	2

Corepro LEDtube HF, Instant Fit 1500mm 2000lm
Model number / EOC code: 9290012497 / 871869659203800 9290012498 / 871869659205200
AC (50Hz) on HF Ballast Compatible

CorePro LEDtube Universal HO - 1200 mm

Ballast Compatibility



KEY

	Ballast is compatible
	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



<p style="text-align: center;">CorePro LEDtube UN 1200mm HO 18W8xx T8</p> <p style="text-align: center;">Model number / EOC code: 9290018692A / 871869680166600 9290018693A / 871869680168000 9290018694A / 87186968017030</p>
--

	Ballast type	10nc / Ref. no.	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
PHILIPS	EB-C 136 TL-D 220-240	9137131992	1	
	EB-S 236 TL-D 220-230	9137130216	2	
	HF-B 136 TLD 220-240	9137001122	1	
	HF-B 136 TLD EII 220-240	9137001926	1	
	HF-B 236 TL-D 220-240	9137001124	2	
	HF-B 236 TLD EII 220-240	9137001928	2	
	HF-E 136 TL-D II	9137130410	1	
	HF-E 236 TL-D	9137130391	2	
	HF-E 236 TL-D II	9137130411	2	
	HF-K 136 TLD 220-240	9137001477	1	
	HF-P 136 TL-D III IDC	9137130315	1	
	HF-P 236 TL-D III IDC	9137130316	2	
	HF-P 336 TL-D III IDC	9137130317	3	
	HF-P Xt 136 TLD EII 220-240	9137006177	1	
	HF-P XT 236 TLD EII 220-240	9137006178	2	
	HF-P 136 TLD EII 220-240	9137001911	1	
	HF-P 236 TLD 230-240	9137001112	2	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	9137006240	1	
	HF-R 136 TL-D EII	9137006092	1	
	HF-R 236 TL-D EII	9137006093	2	
	HF-R 136 TL-D 220-240V 50/60Hz	9137001117	1	
	HF-R 236 TL-D 220-240V 50/60Hz	9137001120	2	
	HF-Ri TD 1 14/21/24/39TL5 E+	9137006983	1	
	HF-Ri TD 2 14/21/24/39TL5 E+	9137006984	2	
	HF-S 136 TL-D II	9137130321	1	
	HF-S 236 TL-D II	9137130324	2	
	HF-S 336 TL-D II	9137130327	3	
	HF-P 118/136 TL-D III	9137130315	1	
	HF-S 118/136 TL-D II	9137130321	1	
	HF-P 136 TLD 220-240	9137001727	1	
HF-P 138 TLD 220-240	9137001220	1		
HF-P 218/236 TL-D III	9137130316	2		
HF-S 218/236 TL-D II	9137130324	2		
OSRAM	QT-FIT8 1x36		1	
	QT-FIT8 2x36		2	
	QTP8 1x36		1	
	QTP8 2x36		2	
	QTP-OPTIMAL 1x18-40		1	
	QTP-OPTIMAL 2x18-40		2	
	QT-FIT 5/8 2x18-39		2	
HELVAR	EL1x36/40/18S		1	
	EL1x36HF		1	
	EL1x36ngn		1	
	EL2x36/40s		2	
	EL2x36ngn		2	
TRIDONIC ATCO	PC 1/36 T8 INDUSTRY	86458035	1	
	PC 1/36 T8 PRO	22176217	1	
	PC 1x36 T8 PRO lp	22185214	1	
	PC2/36 T8 INDUSTRY	86458036	2	
	PC2x36 T8 PRO sl	22185217	2	
	PC 2x36 T8 TOP sl	22185226	2	
	PC 1x36 T8 TOP sl	22185223	1	
	PC1/36 T8 PRO sc	89800008	1	
	PC 3/36 T8 PRO	22176231	3	

CorePro LEDtube Universal HO - 1200 mm



Ballast Compatibility

KEY

	Ballast is compatible
	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
	ELXe 238.527	188137	1
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Trilux	D36.2-23021 E		2
	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains (only one single side supply)		1

CorePro LEDtube UN 1200mm HO 18W8xx T8
Model number / EOC code: 9290018692A / 871869680166600 9290018693A / 871869680168000 9290018694A / 871869680170300
AC (50Hz) on HF Ballast Compatible
•
•
•
•
•
•

General note Philips CorePro LEDtube Universal HO

General notes: Philips LEDtubes Universal T8 are designed to work on HF ballasts, or EM ballast, or direct mains connection.

For HF ballast connection: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes Universal T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes Universal T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with HF ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Philips CorePro LEDtubes Universal HO are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

For EM ballasts or direct mains connection: Please refer to the installation guide.

CorePro LEDtube Universal HO - 1500 mm

Ballast Compatibility



KEY

Ballast is compatible
• Ballast is compatible, light output may differ >10% compared to specifications
Ballast is not compatible
Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



			CorePro LEDtube UN 1500mm HO 18W8xx T8	
			Model number / EOC code: 9290018692A / 871869680166600 9290018693A / 871869680168000 9290018694A / 871869680170300	
			AC (50Hz) on HF Ballast Compatible	
Ballast type	10nc / Ref. no.	Lamps on ballast		
PHILIPS	EI 158 TL-D 220-240	9137 006 075	1	
	HF-B 158 TLD 220-240	9137 001 123	1	
	HF-B 158 TLD EII 220-240	9137 001 927	1	
	HF-B 258 TLD 220-240	9137 001 125	2	
	HF-B 258 TL-D EII 220-240	9137 001 929	2	
	HF-E 158 TL-D	9137 130 389	1	
	HF-E 1/2 58 TL-D II	9137 130 409	2	
	HF-E 1/2 58 TL-D II	9137 130 409	1	
	HF-P 154/155 TL5 HO/PL-L III IDC	9137 130 282	1	
	HF-P 158 TLD EII 220-240	9137 001 912	1	
	HF-P 158 TL-D III IDC	9137 130 318	1	
	HF-P 258 TLD EII 220-240	9137 001 916	2	
	HF-P 258 TL-D III IDC	9137 130 319	2	
	HF-P Xt 158 TLD EII 220-240	9137 006 179	1	
	HF-P Xt 258 TL-D EII 220-240	9137 006 180	2	
	HF-P 158 TLD 220-240	9137 001 185	1	
	HF-P 258 TLD 230-240	9137 001 110	2	
	HF-R 158 TLD 220-240	9137 001 118	1	
	HF-R 258 TLD 220-240	9137 001 119	2	
	HF-R 158 TLD EII	9137 006 094	1	
	HF-R 258 TLD EII	9137 006 095	2	
	HF-R TD 258 TLD EII 220-240	9137 006 070	2	
	HF-RITD 1 28/35/49/54TL5 E+	9137006956	1	
	HF-RITD 2 28/35/49/54TL5 E+	9137006958	2	
	HF-S 158		1	
	HF-S 158 TL-D II	9137 130 322	1	
	HF-S 158 TL-D II 220-240V 50/60Hz	9137 130 322	1	
	HF-S 258 TL-D II	9137 130 325	2	
	HF-S 258 TL-D II HT	9137 006 899	2	
	HF-S 158 TLD 220-240	9137 006 319	1	
	EB-P 258 TLD ICC 220-240	9137 130 210	2	
	HF-P 258 TLD 220-240	9137001206	2	
OSRAM	QT Deluxe HF 1x58 230-240 DIM		1	
	QT Deluxe HF 2x58 230-240 Dim		2	
	QT-FIT8 1x58 - 70		1	
	QT-FIT8 2x58 70		2	
	QTP8 1x58		1	
	QTP8 2x58		2	
	QTP-OPTIMAL 1x54-58		1	
	QTP OPTIMAL 2x54 58		2	
	QT 1X58 DIM		1	
	QT-FIT 5/8 1x54-58		1	
	QT-FIT 5/8 2x54-58		2	
	QT-FIT8 2x54-58		2	
	HELVAR	EL1x58ngn		1
EL1x58s			1	
EL2x58es			2	
EL2x58HF			2	
EL2x58ngn			2	
EL2x58s			2	
TRIDONIC ATCO	PC 1/58 T8 INDUSTRY	86 458 037	1	
	PC 1/58 T8 PRO	22 176 094	1	
	PC 1x58 T8 PRO Ip	22 185 215	1	
	PC 2/58 T8 INDUSTRY	86 458 038	2	
	PC 2x58 E011		2	
	PC 2x58 E011 IDC	22 083 174	2	
	PC 2x58 T8 PRO sl	22 185 218	2	
	PC 1x58 T8 TOP sl	22185224	1	
	PC 2x58 T8 TOP sl	22185227	2	
	PCA 1/58 excel one4all	22 085 286	1	
	PCA 2x58 EXCEL One4all Ip	28 000 040	2	

CorePro LEDtube Universal HO - 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
•	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 158.201	188315	1
	ELXc 158.209	188706	1
	ELXc 158.218	188870	1
	ELXc 258.203	188317	2
	ELXc 258.210	188707	2
	ELXc 258.219	188871	2
	ELXe 258.222	188130	2
	ELXe 258.222	188130	1
	ELXe 158.524	188024	1
BAG-HUECO	BCD58.1F-01/220-240/1-10V	1009 7145	1
	BCS58.1FX-11/220-240	1007 7592	1
	BCS58.2FX-11/220-240	1007 7593	2
	BCS58.2SX-01/220-240	1005 1003	2
	BCS58.1SR-01/220-240		1
	D 58.1-23021 E	166 072	1
	D 58.2-23021 E	166 082	2
	SCS58.2SR-11/220-240	166 272	2
Trilux	D58.1-23021E		1
	DD58.1-23031E		1
	D58.2-23021E		2
May + Christie	MCU 158		1
	MCU 258		2
Others	Direct Mains (only one single side supply)		
	Electro Magnetic Ballast		

CorePro LEDtube UN
1500mm HO
18W8xx T8

Model number / EOC code:
9290018695A / 871869680172700
9290018696A / 871869680174100
9290018697A / 871869680176500

AC (50Hz) on HF Ballast Compatible

General note Philips CorePro LEDtube Universal HO

General notes: Philips LEDtubes Universal T8 are designed to work on HF ballasts, or EM ballast, or direct mains connection.

For HF ballast connection: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes Universal T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes Universal T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with HF ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Philips CorePro LEDtubes Universal HO are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

For EM ballasts or direct mains connection: Please refer to the installation guide.



© 2020 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

04/2020
Data subject to change.

www.philips.com/LEDtube