

Cloud L2+ Managed Fiber Switch

WI-CGS5026



Hardware version: V2.0

Overview

Wi-Tek Cloud L2+ Managed Fiber Switches provide a more efficient, simple, secure and easy-to-use remote management method, which facilitates management and maintenance. Wi-Tek cloud L2+ switches support intelligent deployment, automatic configuration networking, abnormal alarm and other functions. No professional IT operation and maintenance personnel are required, and novices can easily get started. In addition, it supports flexible 802.1Q VLAN, port aggregation, ERPS, static routing, DHCP server, QoS and bandwidth control. Wi-Tek Cloud L2+ Managed Fiber Switches are cost-effective networking solutions for small and medium-sized businesses.

Features

Flexible VLAN Division

In the enterprise office network, to isolate network access between different departments to avoid PCs infected by viruses affecting the entire network, it is necessary to divide the interior into different VLANs to isolate the broadcast domain and improve the stability of the network. Wi-Tek Cloud L2+ Managed Fiber Switch provides a convenient and flexible way to divide VLANs, allowing you to assign the ports to different VLANs as needed. Users in different VLANs do not affect each other, creating a more stable network for the users.

Network Quality Guarantee

The switch applies rich QoS policies to integrate voice, data, and video services on one network. Administrators can designate the traffic's priority based on various means, including Port Priority, 802.1P Priority, and DSCP Priority, to ensure that voice and video are always clear and smooth.

High Reliability

Support STP/ RSTP/ MSTP Layer 2 protection technology to ensure the stability of the local area network and include a backup connection to prevent when a working line fails, automatically provide a backup path to ensure that the local network is online for a long time, and network administrators can also effectively suppress broadcast storms through IGMP Snooping technology.


Cloud Management

Wi-Tek Cloud L2+ Managed Fiber Switch not only supports web interface and CLI management but also supports Wi-Tek Cloud management. Users can view the monitoring network status, make remote configurations, and troubleshoot anywhere and anytime.

Specifications



Model	WI-CGS5026
Hardware Version	V2.0
Hardware Features	
Interfaces	
Downlink Ports	8 x 10/100/1000Mbps RJ45 Ports
Uplink Ports	18 x 1000Mbps SFP Slots
Management Port	1 x Console port
Performance	
Memory and Flash	128MB DRAM, 32MB Flash
Switch Property	
Standards and Protocols	IEEE 802.3i, IEEE802.3u, IEEE802.3ab, IEEE 802.3z, IEEE802.1D, IEEE802.1W, IEEE802.1S, IEEE802.1Q, IEEE802.3ad, IEEE802.1X, IEEE802.1p
Forwarding Mode	Store and Forward
Switching Capacity	52 Gbps
Packet Forwarding Rate	38.69 Mpps
MAC Address Table	8 k
Jumbo Frame	10 kB
Power Supply	
Input Power	AC 100–240V, 50/60Hz
Power Consumption	Idle: 115V 60Hz–41.6W 230V 50Hz–40.5W



Model		WI-CGS5026
Physical Characteristics		
LED Indicators		<p>PWR Indicator:</p> <p>On: the device power on is normal</p> <p>Off: the device is power off or failed</p> <p>SYS Indicator:</p> <p>Off: The system is being started or abnormal</p> <p>Blinking: The system is working normally</p> <p>LNK/ACT Indicator (port 1–26):</p> <p>On: Port connected</p> <p>Off: Port disconnected</p> <p>Blinking: Data transmission</p>
Buttons		Reset: Hold for >5 sec. to restore factory default
Fan Quantity		1
Dimensions (W*D*H)		<p>Switch Dimension: 283*180*44mm</p> <p>Package Dimension: 370*230*80mm</p>
Weight		<p>Net Weight: 1.7kg</p> <p>Package Weight: 2.27kg</p>
Installation		Rack-Mount, Desktop
Reliability	Surge Immunity	<p>Differential mode: 4kV</p> <p>Common mode: 2kV</p>
	ESD Protection	<p>Contact discharge: 6kV</p> <p>Air discharge: 8kV</p>
Operating Temperature		-10°C to 50C(14°F to 122°F)
Storage Temperature		-40 to 70°C(-40°F to 158°F)
Operating Humidity		10% to 90% RH non-condensing
Storage Humidity		5% to 90% RH non-condensing
Certification		
Certification		CE, FCC, RoHS, UKCA, RCM




Model	WI-CGS5026
Software Features	
QoS	8 priority queues
	802.1p CoS/DSCP priority
	Queue scheduling(SP (Strict Priority);WRR (Weighted Round Robin);SP+WRR
	Bandwidth Control(Port/Flow based Rating Limiting)
	Policy Config
	Class-Map Config
	Policy-Map Config
	Policy Mark Config
	Policy Bandwidth
	Policy VLAN
L2+	IPv4/IPv6 Interfaces
	Static Routing(512 static routes)
	Static ARP
	8K ARP Entries
	ARP timeout
	Gratuitous ARP
	DHCP Server
	DHCP Relay
DHCP L2 Relay	
Link Aggregation	Static link aggregation
	802.3ad LACP
	Up to 8 aggregation groups and up to 8 ports per group
Spanning Tree Protocol	802.1d STP
	802.1w RSTP
	802.1s MSTP
	STP Security: TC Protect, BPDU Filter, BPDU Protect, Root Protect, Loop Protect
Loopback Detection	Port-based
	VLAN based




Model	WI-CGS5026
Flow Control	802.3x Flow Control
	HOL Blocking Prevention
Mirroring	Port Mirroring
	CPU Mirroring
	One-to-One
	Many-to-One
	Tx/Rx/Both
L2 Multicast	Supports IPv4/IPv6 IGMP groups
	IGMP Snooping
	IGMP v1/v2/v3 Snooping
	Immediately-leave
	IGMP Snooping Querier
	IGMP Authentication
	IGMP Proxy
	MVR
	MLD Snooping
	MLD v1/v2 Snooping
	Immediately-leave
	MLD Snooping Querier
	Static Group Config
	Limited IP Multicast
Multicast Filtering	



Model	WI-CGS5026
VLAN	VLAN Group
	Max. 4K VLAN Groups
	802.1Q tag VLAN
	MAC VLAN
	Protocol VLAN
	GVRP
	Voice VLAN
	Port-Based QinQ
	Tunnel TPID (0x8100, 0x9100, 0x9200, Protocol ID)
	OUI-Based VLAN
	Access Control List
Source MAC	
Destination MAC	
Packet Type (Untagged-eth2, Untagged-802.3, Tagged-eth2, Tagged-802.3)	
VLAN ID	
Ether Type	
IP ACL	
Source IP	
Destination IP	
Fragment Packet	
IP Protocol	
IP Precedence	
TCP/UDP Port	
DSCP/IP TOS	
Combined ACL	
IPv6 ACL	
icmp/tcp/udp	




Model	WI-CGS5026
Access Control List	Mirroring
	Attached Direction(Ingress/Traffic-statistic)
	QoS Remark
	ACL apply to Port/VLAN
	Time-based ACL
Security	IP-MAC-Port Binding
	DHCP Snooping
	ARP Inspection
	IPv4 secure-port
	DHCPv6 Snooping
	snooping remote-id
	snooping subscriber-id
	IPv6 security-ra
	DoS Defend
	DHCP Filter
	Static/Dynamic Port Security
	Broadcast/Multicast/Unicast Storm Control
	kpps/pps control mode
	802.1X
	Port base authentication
	Mac base authentication
	VLAN Assignment
	Guest VLAN
	Support RADIUS authentication and accountability
	AAA (including TACACS+)
	Port Isolation
	Secure web management through HTTPS with SSLv3/TLS 1.2
	Secure Command Line Interface (CLI) management with SSHv1/SSHv2
IP/Port/MAC-based access control	



Model	WI-CGS5026
IPv6	IPv6 Dual IPv4/IPv6
	Multicast Listener Discovery (MLD) Snooping
	IPv6 ACL
	IPv6 Interface
	Static IPv6 Routing
	IPv6 neighbor discovery (ND)
	Path maximum transmission unit (MTU) discovery
	Internet Control Message Protocol (ICMP) version 6
	TCPv6/UDPv6
	IPv6 applications
	DHCPv6 Client
	Ping(v6)
	Tracert(v6)
	Telnet(v6)
	IPv6 SNMP
IPv6 SSH	
IPv6 SSL	
Http/Https	
Advanced Features	802.3ah Ethernet Link OAM
	ERPS
	Cloud Management
	ONVIF(ONVIF Detection,ONVIF Server(NLM))
	Batch Firmware Upgrading
	Intelligent Network Monitoring Abnormal Event Warnings
	Automatic Device Discovery
	Support Remote Management
	Support Cloud VLAN Configuration
	Support Topology Display
Support Cloud Control Port Configuration	



WI-CGS5026

Dimensions (mm)



Front Panel

Rear Panel



Package Contents

Welcome to order our products. After purchasing, you will receive:

Items	Quantity
Switch	1 pcs
Quick Installation Guide	1 pcs
Serial line	1 pcs
Power Cord	1 pcs
Mounting Accessories(Hook x 2, MATS x 4, Screw x 8)	1 pcs



Wireless-Tek Technology Limited

Address: Building 3, Units 1801-1807, 1812, Huaqiang Era Plaza, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen City, Guangdong Province, China.

Website: www.wireless-tek.com

Tel: 86-0755-32811290

Email: sales@wireless-tek.com

Technical Support: tech@wireless-tek.com



Technical Support



Cloud Management



Company Website