

EHN711

**Daily time switch 1 channel, analog, 72x72 with power reserve**

**Technical properties**

**Functions**

Number of function channels	1
Switching cycles	min. 50000

**Configuration**

Switch mode	change-over contact, usable as NC or NO
Number of modules	4

**Controls and indicators**

Manual selection switches / push-buttons	as rotary switch for temporary on/off switching
--	---

**Main electrical features**

Rated operational voltage Ue	230 / 240 V
Frequency	50/60 Hz

**Voltage**

Operating voltage	230 V~
-------------------	--------

**Electric current**

Switching current at $\cos \varphi = 0.6$	max. 3 A
---	----------

**Dimensions**

Depth of installed product	48.5 mm
Height of installed product	72 mm
Dimensions (LLxwxhh)	72 x 72 x 48,5
Width of installed product	72 mm

**Power**

Power consumed	0.5 VA
Power consumption (operation)	0.5 VA
Total power loss under IN	1 W
Loss power at full load	≈ 1 W

**Battery**

Battery / storage battery	with integrated storage battery for power reserve
Charging time of the power reserve in hours	120

**Incandescent bulbs control**

Max. power with incandescent lamps	1000 W
230 V incandescent lamps and halogen lamps	max. 1000 W

**Installation, mounting**

Installation mode	for surface mounting
-------------------	----------------------

**Connection**

Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 6mm <sup>2</sup>
Conductor cross-section (flexible)	1...6 mm <sup>2</sup>
Conductor cross-section (rigid)	1...6 mm <sup>2</sup>
Number of contacts	1
Type of contacts	1 changeover
Type of connection	with screw terminals
Contact	with potential-free switching contact
Type of connection	with screw

**Settings**

Number of program steps	72
Summer / Winter time change	manual
Shortest switching time	10 mn
Type of programming	analog
Program cycles	Programme cycle: 24 hours
Programming cycle	24H
Setting	Setting via day dial
Astro program	No

**Equipment**

Number of channels	1
Number of switching times for on/off	72
Supply failure reserve	200 h
Switching cycles at $\cos \varphi = 0,6$	min. 20000

**Use**

Cycle	daily
-------	-------

**Safety**

Halogen free	Yes
--------------	-----

**Use conditions**

Operating temperature	-10...50 °C
Working accuracy	1
Storage/transport temperature	-20...60 °C