

WIRE END FERRULE CRIMPING BOX, ISO FR2

Article number: 187602

The wire end ferrule box contains insulated wire end ferrules in various sizes. The ferrules are color-coded according to color series 2 and the set contains ferrules in the sizes 0.5 mm² x 8 mm (50 pieces), 0.75 mm² x 8 mm (100 pieces), 1 mm² x 8 mm (100 pieces), 1.5 mm² x 8 mm (100 pieces) and 2.5 mm² x 8 mm (50 pieces). The shaker box makes it easy to remove and store the ferrules. The insulated ferrules provide a secure and reliable connection of cable ends and protect against short circuits. Additional features: The ferrules are made of E-copper, tin-plated, the insertion funnel is made of polypropylene and is heat-resistant up to 105 °C. The tin coating of the ferrules is 3 µm.

Length (mm)	90 mm
Width (mm)	42 mm
Height (mm)	90 mm
Weight (kg)	0,1 kg



Attribute	Value
Housing color	farblos
Material of the housing	Kunststoff
With tool	No
Compression cable lugs for copper conductors	No
Tubular cable lugs for copper conductors	No
Cable glands	No
Insulated wire end ferrules	Yes
Insulated cable connections	No
Non-insulated ferrules	No
Non-insulated cable connections	No
Material quality of the housing	Polyamid (PA)
With transparent lid	Yes
With cable tie	No

GTIN: 4021103114483

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de