

MPC-Quick fasteners+

with internal thread, galvanised

Application

- Secure and easy installation in slot of MPC-Support channel in order to attach mounting accessories
- For use in dry interiors

Your advantages









- Time-saving attachment in the channel slot, even if subsequently fitted between existing pipe sections
- Simple and secure handling: insert in the MPC-Support channels - turn - and the MPC-Quick fastener is fixed. No slipping, no falling out
- High quality and load capacity



For profiles 27/18 and 28/30



For profiles 38/24 to 40/120



Features



For profiles	Connecting thread	Max. recommended tensile load F_z [N]	Max. recommended load lateral (displacement) F_a [N]	Tightening torque [Nm]
27/18 L	M8	1,000	200	7
	M10		300	
27/18	M8	1,750	200	
	M10		300	
28/30	M8	2,500	200	9
	M10		300	
38/24	M8	2,000	200	
	M10		300	
38/40, 38/80	M8	2,800	400	17
	M10			9
39/52	M8	3,300		17
	M10			9
40/60, 40/80, 40/120	M8	4,000	600	17
	M10			9

For profiles	Connecting thread	Part no.	Sales unit	Pack unit
27/18, 28/30	M8	175766	100	Pieces
	M10	175771		
38/24-40/120	M8	175463		
	M10	175464		